## NSN 5330-01-181-2525

Gasket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5330-01-181-2525

| Cross Sectional Shape:  |
|---|
| Solid single or composition   |
| Hole Diameter:  |
| 0.250 inches  |
| Overall Length:   |
| 6.000 inches  |
| Overall Width:  |
| 4.625 inches  |
| Inside Corner Radius:   |
| 0.438 inches  |
| Outside Corner Radius:  |
| Between 0.125 inches and 0.188 inches   |
| Aperture Width:   |
| 3.375 inches  |
| Aperture Length:  |
| 4.750 inches  |
| Center To Center Distance Between Bolt Holes Along Width:   |
| 2.000 inches  |
| Center To Center Distance Between Bolt Holes Along Length:  |
| 2.126 inches  |
| Outside Edge To Bolt Hole Center Distance Along Width:  |
| 0.312 inches  |
| Outside Edge To Bolt Hole Center Distance Along Length:   |
| 0.312 inches  |
| Cross-sectional Thickness:  |
| Between 0.023 inches and 0.037 inches   |
| Bolt Hole Quantity:   |
| 8   |
| Material:   |
| Rubber butadiene-acrylonitrile class nbr and plastic polyamide or rubber synthetic and cotton   |
| Material Specification:   |
| Ams3274.Navicp-mech has authorized the replacement material for the cancelled material mil-c-8068 military specification 1st material   |
| response  |
| Style Designator:   |
| Non-circular Section 1. The section |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del></del>   |
| Demilitarization:   |
| No  |
| Fiig:   |

A032a0

## NSN 5330-01-181-2525

Gasket - Page 2 of 2



Mil-std (military Standard):

Mil-c-8068 spec.