## NSN 5330-01-192-8642

Preformed Packing - Page 1 of 1

Mil-p-25732 spec.



View Online at https://aerobasegroup.com/nsn/5330-01-192-8642
Tempurature Rating:
-65.0 degrees fahrenheit and 275.0 degrees fahrenheit
Cross-sectional Height:
Between 0.135 inches and 0.143 inches
Center Hole Diameter:
Between 4.844 inches and 4.874 inches
Peripheral Diameter:
5.137 inches
Elongation Percentage:
160
Hardness Rating:
70.0 shore durometer a and 80.0 shore durometer a
Criticality Code Justification:
Zzzw
Material:
Rubber butadiene-acrylonitrile class nbr
Special Test Features:
Special quality control testing
Test Data Document:
81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Departure From Cited Document:
As modified by material which must conform to ships parts control center special quality control provisions
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A032a0
Mil-std (military Standard):