

View Online at <https://aerobasegroup.com/nsn/5330-01-206-9698>

Cross Sectional Shape:

Solid single or composition

Hole Diameter:

4.8 millimeters

Overall Length:

65.0 millimeters

Overall Width:

22.0 millimeters

Inside Corner Radius:

0.4 millimeters

Aperture Width:

16.0 millimeters

Aperture Length:

42.0 millimeters

Center To Center Distance Between Bolt Holes Along Width:

12.0 millimeters

Center To Center Distance Between Bolt Holes Along Length:

55.0 millimeters

Outside Edge To Bolt Hole Center Distance Along Width:

5.0 millimeters

Outside Edge To Bolt Hole Center Distance Along Length:

5.0 millimeters

Cross-sectional Thickness:

Between 0.7 millimeters and 0.9 millimeters

Bolt Hole Quantity:

4

Hardness Rating:

55.0 shore durometer a and 65.0 shore durometer a

Material:

Plastic polyamide and rubber synthetic or rubber chloroprene class cr

Material Specification:

Mil-c-8068 military specification 1st material response and mil-c-8068 military specification 2nd material response or fairprene 22-002, fscm 90227 mfr ref 1st material response and fairprene 22-002, fscm 90227 mfr ref 2nd material response or reeves cote 7220, fscm 86732 mfr ref 1st material response and reeves cote 7220, fscm 86732 mfr ref 2nd material response or 417, sc715abc1e3f1z military standard 3rd material response

Style Designator:

Non-circular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A032a0

Mil-std (military Standard):

Mil-c-8068 spec.