NSN 5330-01-215-0131

Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-01-215-0131

| Cross Sectional Shape: |
|--|
| Metal and synthetic rubber |
| Hole Diameter: |
| Between 0.278 inches and 0.287 inches |
| Bolt Circle Diameter: |
| Between 1.648 inches and 1.708 inches |
| End Radius: |
| Between 1.928 inches and 2.008 inches |
| Aperture Diameter: |
| Between 0.659 inches and 0.679 inches |
| Outside Corner Radius: |
| Between 0.280 inches and 0.300 inches |
| Cross-sectional Thickness: |
| Between 0.106 inches and 0.140 inches |
| Gage Ring Thickness: |
| Between 0.070 inches and 0.090 inches |
| Elongation Percentage: |
| 120 |
| Hardness Rating: |
| 75.0 shore durometer a |
| Special Features: |
| Aluminum surfaces anodized per mil-a-8625, type 2 |
| Material: |
| Aluminum alloy 6061 and rubber fluorocarbon class fpm |
| Material Specification: |
| Ams 4027 assn standard 1st material response and mil-r-83485 military specification 2nd material response or a50tf193 cl a, fscm 07482 |
| mfr ref 2nd material response |
| Style Designator: |
| Triangle |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A032a0 |
| Mil-std (military Standard): |
| Mil-r-83485 spec. |