## NSN 5330-01-217-2877

Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-01-217-2877

| Cross Sectional Shape:                                                                                   |
|----------------------------------------------------------------------------------------------------------|
| Metal and synthetic rubber                                                                               |
| Hole Diameter:                                                                                           |
| Between 0.278 inches and 0.287 inches                                                                    |
| Bolt Circle Diameter:                                                                                    |
| 1.240 inches                                                                                             |
| End Radius:                                                                                              |
| 1.530 inches                                                                                             |
| Aperture Diameter:                                                                                       |
| Between 0.302 inches and 0.322 inches                                                                    |
| Outside Corner Radius:                                                                                   |
| Between 0.280 inches and 0.300 inches                                                                    |
| Cross-sectional Thickness:                                                                               |
| Between 0.106 inches and 0.140 inches                                                                    |
| Gage Ring Thickness:                                                                                     |
| Between 0.070 inches and 0.090 inches                                                                    |
| Material:                                                                                                |
| Rubber fluorocarbon class fpm and aluminum alloy 6061                                                    |
| Material Specification:                                                                                  |
| A50tf193 cl-a, fscm 95272 mfr ref 1st material response and ams 4027 assn standard 2nd material response |
| Surface Treatment:                                                                                       |
| Anodize                                                                                                  |
| Surface Treatment Specification:                                                                         |
| Mil-a-8625, type 2, cl 1 military specification single treatment response                                |
| Style Designator:                                                                                        |
| Triangle                                                                                                 |
| Shelf Life:                                                                                              |
| N/a                                                                                                      |
| Unit Of Measure:                                                                                         |
| <del></del>                                                                                              |
| Demilitarization:                                                                                        |
| No                                                                                                       |
| Fiig:                                                                                                    |
| A032a0                                                                                                   |
| Mil-std (military Standard):                                                                             |
| Mil-a-8625 spec.                                                                                         |
|                                                                                                          |