## NSN 5330-01-239-2416

Gasket - Page 1 of 1

A032a0



| View Online at https://aerobasegroup.com/nsn/5330-01-239-2416   |
|---|
| Cross Sectional Shape:  |
| Solid single or composition   |
| Hole Diameter:  |
| Between 0.300 inches and 0.340 inches   |
| Overall Width:  |
| Between 4.800 inches and 4.880 inches   |
| Aperture Diameter:  |
| Between 2.440 inches and 2.480 inches   |
| Outside Corner Radius:  |
| Between 0.400 inches and 0.440 inches   |
| Side Radius From Gasket Center:   |
| Between 1.650 inches and 1.660 inches   |
| Cross-sectional Thickness:  |
| Between 0.030 inches and 0.050 inches   |
| Bolt Hole Quantity:   |
| 4   |
| Hardness Rating:  |
| 35.0 shore durometer a and 40.0 shore durometer a   |
| Special Features:   |
| Ctr of three bolt holes located 4.000 in. From ctr of gasket, ctr of fourth bolt hole located 0.125 in. Below ctr |
| Material:   |
| Rubber silicone class q   |
| Material Specification:   |
| Zz-r-765 gr 40, cl 2b federal specification single material response  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |