## NSN 5330-01-250-5275

Gasket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5330-01-250-5275

| Cross Sectional Shape:                                      |
|---|
| Solid single or composition                                 |
| Hole Diameter:  |
| Between 0.110 inches and 0.130 inches                       |
| Overall Length:   |
| Between 1.023 inches and 1.039 inches                       |
| Overall Width:  |
| Between 1.023 inches and 1.039 inches                       |
| Aperture Diameter:  |
| Between 0.750 inches and 0.766 inches                       |
| Outside Corner Radius:                                      |
| Between 0.131 inches and 0.151 inches                       |
| Center To Center Distance Between Bolt Holes Along Width:   |
| Between 0.740 inches and 0.760 inches                       |
| Center To Center Distance Between Bolt Holes Along Length:  |
| Between 0.740 inches and 0.760 inches                       |
| Outside Edge To Bolt Hole Center Distance Along Width:      |
| Between 0.140 inches and 0.142 inches                       |
| Outside Edge To Bolt Hole Center Distance Along Length:     |
| Between 0.140 inches and 0.142 inches                       |
| Cross-sectional Thickness:                                  |
| Between 0.026 inches and 0.036 inches                       |
| Bolt Hole Quantity:   |
| 4   |
| Elongation Percentage:                                      |
| 125   |
| Hardness Rating:  |
| 45.0 shore durometer a and 55.0 shore durometer a           |
| Color:  |
| Blue  |
| Material:   |
| Rubber fluorosilicone class fq                              |
| Material Specification:                                     |
| Mil-r-25988 military specification single material response |
| Style Designator:   |
| Non-circular  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |

No

## NSN 5330-01-250-5275

Gasket - Page 2 of 2

Fiig:

A032a0

Mil-std (military Standard):

Mil-r-25988 spec.

