## NSN 5330-01-293-5340

Plain Seal - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-01-293-5340

Accommodated Shaft Diameter:  5.526 inches  Seal Width:  0.366 inches  Housing Bore Diameter:  6.000 inches  Construction:  Two-piece  Special Features:  Min hydraulic pressure 5000 psi; temp: -65 degrees to 250 degrees f; must perform for 10, 000 cycles with displacements of 36 inches and speeds up to 50 ft/sec; must not cause appreciable wear on slding parts as determined by circumferential and longitudinal readings of surface roughness iaw ansi b46.1-85 and changes in dia  Material:  Rubber carboxylic-nitrile-butadiene class xnbr inner ring  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No
Seal Width: 0.366 inches  Housing Bore Diameter: 6.000 inches  Construction: Two-piece  Special Features: Min hydraulic pressure 5000 psi; temp: -65 degrees to 250 degrees f; must perform for 10, 000 cycles with displacements of 36 inches and speeds up to 50 ft/sec; must not cause appreciable wear on slding parts as determined by circumferential and longitudinal readings of surface roughness iaw ansi b46.1-85 and changes in dia  Material: Rubber carboxylic-nitrile-butadiene class xnbr inner ring  Shelf Life: N/a  Unit Of Measure: Demilitarization:
0.366 inches  Housing Bore Diameter: 6.000 inches  Construction: Two-piece  Special Features: Min hydraulic pressure 5000 psi; temp: -65 degrees to 250 degrees f; must perform for 10, 000 cycles with displacements of 36 inches and speeds up to 50 ft/sec; must not cause appreciable wear on slding parts as determined by circumferential and longitudinal readings of surface roughness iaw ansi b46.1-85 and changes in dia  Material: Rubber carboxylic-nitrile-butadiene class xnbr inner ring  Shelf Life: N/a  Unit Of Measure:  Demilitarization:
Housing Bore Diameter:  6.000 inches  Construction: Two-piece  Special Features: Min hydraulic pressure 5000 psi; temp: -65 degrees to 250 degrees f; must perform for 10, 000 cycles with displacements of 36 inches and speeds up to 50 ft/sec; must not cause appreciable wear on slding parts as determined by circumferential and longitudinal readings of surface roughness iaw ansi b46.1-85 and changes in dia  Material: Rubber carboxylic-nitrile-butadiene class xnbr inner ring  Shelf Life: N/a  Unit Of Measure: Demilitarization:
Construction: Two-piece Special Features: Min hydraulic pressure 5000 psi; temp: -65 degrees to 250 degrees f; must perform for 10, 000 cycles with displacements of 36 inches and speeds up to 50 ft/sec; must not cause appreciable wear on slding parts as determined by circumferential and longitudinal readings of surface roughness iaw ansi b46.1-85 and changes in dia Material: Rubber carboxylic-nitrile-butadiene class xnbr inner ring Shelf Life: N/a Unit Of Measure: Demilitarization:
Construction: Two-piece Special Features: Min hydraulic pressure 5000 psi; temp: -65 degrees to 250 degrees f; must perform for 10, 000 cycles with displacements of 36 inches and speeds up to 50 ft/sec; must not cause appreciable wear on slding parts as determined by circumferential and longitudinal readings of surface roughness iaw ansi b46.1-85 and changes in dia Material: Rubber carboxylic-nitrile-butadiene class xnbr inner ring Shelf Life: N/a Unit Of Measure: Demilitarization:
Two-piece  Special Features:  Min hydraulic pressure 5000 psi; temp: -65 degrees to 250 degrees f; must perform for 10, 000 cycles with displacements of 36 inches and speeds up to 50 ft/sec; must not cause appreciable wear on slding parts as determined by circumferential and longitudinal readings of surface roughness iaw ansi b46.1-85 and changes in dia  Material:  Rubber carboxylic-nitrile-butadiene class xnbr inner ring  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:
Special Features:  Min hydraulic pressure 5000 psi; temp: -65 degrees to 250 degrees f; must perform for 10, 000 cycles with displacements of 36 inches and speeds up to 50 ft/sec; must not cause appreciable wear on slding parts as determined by circumferential and longitudinal readings of surface roughness iaw ansi b46.1-85 and changes in dia  Material:  Rubber carboxylic-nitrile-butadiene class xnbr inner ring  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:
Min hydraulic pressure 5000 psi; temp: -65 degrees to 250 degrees f; must perform for 10, 000 cycles with displacements of 36 inches and speeds up to 50 ft/sec; must not cause appreciable wear on slding parts as determined by circumferential and longitudinal readings of surface roughness iaw ansi b46.1-85 and changes in dia  Material:  Rubber carboxylic-nitrile-butadiene class xnbr inner ring  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:
speeds up to 50 ft/sec; must not cause appreciable wear on slding parts as determined by circumferential and longitudinal readings of surface roughness iaw ansi b46.1-85 and changes in dia  Material:  Rubber carboxylic-nitrile-butadiene class xnbr inner ring  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:
surface roughness iaw ansi b46.1-85 and changes in dia  Material: Rubber carboxylic-nitrile-butadiene class xnbr inner ring  Shelf Life: N/a Unit Of Measure: Demilitarization:
Material: Rubber carboxylic-nitrile-butadiene class xnbr inner ring Shelf Life: N/a Unit Of Measure: Demilitarization:
Rubber carboxylic-nitrile-butadiene class xnbr inner ring  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:
Shelf Life:  N/a Unit Of Measure:  Demilitarization:
N/a Unit Of Measure: Demilitarization:
Unit Of Measure: Demilitarization:
 Demilitarization:
No
Fiig:
A032a0