

View Online at <https://aerobasegroup.com/nsn/5330-01-315-3575>

Cross Sectional Shape:

Solid single or composition

Hole Diameter:

0.281 inches

Overall Length:

3.620 inches

Overall Width:

3.620 inches

Outside Corner Radius:

0.380 inches

Aperture Width:

2.840 inches

Aperture Length:

3.120 inches

Inside Corner Bevel Length Along Width:

0.530 inches

Inside Corner Bevel Length Along Length:

0.530 inches

Center To Center Distance Between Bolt Holes Along Width:

2.938 inches

Center To Center Distance Between Bolt Holes Along Length:

2.938 inches

Outside Edge To Bolt Hole Center Distance Along Width:

0.340 inches

Outside Edge To Bolt Hole Center Distance Along Length:

0.340 inches

Cross-sectional Thickness:

0.062 inches

Bolt Hole Quantity:

4

Criticality Code Justification:

Zzzy

Outside Edge To Inside Edge Smallest Distance Along Width:

0.390 inches

Outside Edge To Inside Edge Smallest Distance Along Length:

0.250 inches

Special Features:

Item must comply with requirements of defense supply center philadelphia production standard no. Po0152nrp

Material:

Rubber chloroprene class cr

Material Specification:

Mil-r-6130 type 2, grade a military specification single material response

Special Test Features:

Special quality control testing

Style Designator:

Non-circular

Test Data Document:

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Reference Number Differentiating Characteristics:

Reference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A032a0

Mil-std (military Standard):

Mil-r-6130 spec.