NSN 5330-01-317-5236

Packing Retainer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-01-317-5236

material response Surface Treatment: Phosphate manganese Surface Treatment Specification: Dod-p-16232 military specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Attachment Method: Round hole Attachment Feature Quantity: 14 Attachment Hole Diameter: 0.281 inches Cross-sectional Height: 0.125 inches Center Hole Diameter: Between 7.156 inches and 7.218 inches Peripheral Diameter: Between 8.844 inches and 8.906 inches Material: Steel comp 1020 Material: Steel comp 1020 Material Specification: Astm a108 assn standard 1st material response or astm a575 assn standard 2nd material response or astm a576 assn standard 3 material response Surface Treatment: Phosphate manganese Surface Treatment Specification: Dod-p-16232 military specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	ross Sectional Shape:
Round hole Attachment Feature Quantity: 14 Attachment Hole Diameter: 0.281 inches Cross-sectional Height: 0.125 inches Center Hole Diameter: Between 7.156 inches and 7.218 inches Peripheral Diameter: Between 8.844 inches and 8.906 inches Material: Steel comp 1020 Material Specification: Astm a108 assn standard 1st material response or astm a575 assn standard 2nd material response or astm a576 assn standard 3 material response Surface Treatment: Phosphate manganese Surface Treatment Specification: Dod-p-16232 military specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	quare/rectangular
Attachment Feature Quantity: 14 Attachment Hole Diameter: 0.281 inches Cross-sectional Height: 0.125 inches Center Hole Diameter: Between 7.156 inches and 7.218 inches Peripheral Diameter: Between 8.844 inches and 8.906 inches Material: Steel comp 1020 Material Specification: Astm a108 assn standard 1st material response or astm a575 assn standard 2nd material response or astm a576 assn standard 3 material response Surface Treatment: Phosphate manganese Surface Treatment Specification: Dod-p-16232 military specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	attachment Method:
Attachment Hole Diameter: 0.281 inches Cross-sectional Height: 0.125 inches Center Hole Diameter: Between 7.156 inches and 7.218 inches Peripheral Diameter: Between 8.844 inches and 8.906 inches Material: Steel comp 1020 Material Specification: Astm a108 assn standard 1st material response or astm a575 assn standard 2nd material response or astm a576 assn standard 3material response Surface Treatment: Phosphate manganese Surface Treatment Specification: Dod-p-16232 military specification single treatment response Shelf Life: N/a Unit Of Measure: — Demilitarization: No Fiig:	cound hole
Attachment Hole Diameter: 0.281 inches Cross-sectional Height: 0.125 inches Center Hole Diameter: Between 7.156 inches and 7.218 inches Peripheral Diameter: Between 8.844 inches and 8.906 inches Material: Steel comp 1020 Material Specification: Astm a108 assn standard 1st material response or astm a575 assn standard 2nd material response or astm a576 assn standard 3 material response Surface Treatment: Phosphate manganese Surface Treatment Specification: Dod-p-16232 military specification single treatment response Shelf Life: N/a Unit Of Measure: — Demilitarization: No Fiig:	attachment Feature Quantity:
Cross-sectional Height: 0.125 inches Center Hole Diameter: Between 7.156 inches and 7.218 inches Peripheral Diameter: Between 8.844 inches and 8.906 inches Material: Steel comp 1020 Material Specification: Astm a108 assn standard 1st material response or astm a575 assn standard 2nd material response or astm a576 assn standard 3 material response Surface Treatment: Phosphate manganese Surface Treatment Specification: Dod-p-16232 military specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	4
Cross-sectional Height: 0.125 inches Center Hole Diameter: Between 7.156 inches and 7.218 inches Peripheral Diameter: Between 8.844 inches and 8.906 inches Material: Steel comp 1020 Material Specification: Astm a108 assn standard 1st material response or astm a575 assn standard 2nd material response or astm a576 assn standard 3 material response Surface Treatment: Phosphate manganese Surface Treatment Specification: Dod-p-16232 military specification single treatment response Shelf Life: N/a Unit Of Measure: — Demilitarization: No Fiig:	attachment Hole Diameter:
0.125 inches Center Hole Diameter: Between 7.156 inches and 7.218 inches Peripheral Diameter: Between 8.844 inches and 8.906 inches Material: Steel comp 1020 Material Specification: Astm a108 assn standard 1st material response or astm a575 assn standard 2nd material response or astm a576 assn standard 3material response Surface Treatment: Phosphate manganese Surface Treatment Specification: Dod-p-16232 military specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig:	.281 inches
Center Hole Diameter: Between 7.156 inches and 7.218 inches Peripheral Diameter: Between 8.844 inches and 8.906 inches Material: Steel comp 1020 Material Specification: Astm a108 assn standard 1st material response or astm a575 assn standard 2nd material response or astm a576 assn standard 3 material response Surface Treatment: Phosphate manganese Surface Treatment Specification: Dod-p-16232 military specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	cross-sectional Height:
Between 7.156 inches and 7.218 inches Peripheral Diameter: Between 8.844 inches and 8.906 inches Material: Steel comp 1020 Material Specification: Astm a108 assn standard 1st material response or astm a575 assn standard 2nd material response or astm a576 assn standard 3 material response Surface Treatment: Phosphate manganese Surface Treatment Specification: Dod-p-16232 military specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	.125 inches
Peripheral Diameter: Between 8.844 inches and 8.906 inches Material: Steel comp 1020 Material Specification: Astm a108 assn standard 1st material response or astm a575 assn standard 2nd material response or astm a576 assn standard 3 material response Surface Treatment: Phosphate manganese Surface Treatment Specification: Dod-p-16232 military specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Center Hole Diameter:
Between 8.844 inches and 8.906 inches Material: Steel comp 1020 Material Specification: Astm a108 assn standard 1st material response or astm a575 assn standard 2nd material response or astm a576 assn standard 3material response Surface Treatment: Phosphate manganese Surface Treatment Specification: Dod-p-16232 military specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	letween 7.156 inches and 7.218 inches
Material: Steel comp 1020 Material Specification: Astm a108 assn standard 1st material response or astm a575 assn standard 2nd material response or astm a576 assn standard 3material response Surface Treatment: Phosphate manganese Surface Treatment Specification: Dod-p-16232 military specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Peripheral Diameter:
Steel comp 1020 Material Specification: Astm a108 assn standard 1st material response or astm a575 assn standard 2nd material response or astm a576 assn standard 3nd material response Surface Treatment: Phosphate manganese Surface Treatment Specification: Dod-p-16232 military specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	letween 8.844 inches and 8.906 inches
Material Specification: Astm a108 assn standard 1st material response or astm a575 assn standard 2nd material response or astm a576 assn standard 3material response Surface Treatment: Phosphate manganese Surface Treatment Specification: Dod-p-16232 military specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	laterial:
Astm a108 assn standard 1st material response or astm a575 assn standard 2nd material response or astm a576 assn standard 3 material response Surface Treatment: Phosphate manganese Surface Treatment Specification: Dod-p-16232 military specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	iteel comp 1020
material response Surface Treatment: Phosphate manganese Surface Treatment Specification: Dod-p-16232 military specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	laterial Specification:
Surface Treatment: Phosphate manganese Surface Treatment Specification: Dod-p-16232 military specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	stm a108 assn standard 1st material response or astm a575 assn standard 2nd material response or astm a576 assn standard 3rd
Phosphate manganese Surface Treatment Specification: Dod-p-16232 military specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	naterial response
Surface Treatment Specification: Dod-p-16232 military specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	surface Treatment:
Dod-p-16232 military specification single treatment response Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	hosphate manganese
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	surface Treatment Specification:
N/a Unit Of Measure: Demilitarization: No Fiig:	od-p-16232 military specification single treatment response
Unit Of Measure: Demilitarization: No Fiig:	shelf Life:
Demilitarization: No Fiig:	l/a
No Fiig:	Init Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	lo
	iig:
A032a0	.032a0
Mil-std (military Standard):	iil-std (military Standard):
spec.	spec.