NSN 5330-01-323-5579

Spiral Wound Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-01-323-5579

Metal winding w/ soft filler and outer ring Tempurature Rating: 900.0 degrees fahrenheit Outside Diameter: 2.719 inches Aperture Diameter: 1.875 inches Bearing Surface Width: 0.422 inches Gage Ring Outside Diameter: 4.825 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.181 inches Maximum Pressure Rating: 2500.0 pounds per square inch Material: Steel outer ring Material Specification: Mill-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and b class and ips11/2 size and 2500 series Shelf Life: Na Unit Of Measure: - Demilitarization: No Fig: Mil-p-24503 spec.	Cross Sectional Shape:
900.0 degrees fahrenheit Outside Diameter: 2.719 inches Aperture Diameter: 1.875 inches Bearing Surface Width: 0.422 inches Bearing Surface Width: 0.422 inches Gage Ring Outside Diameter: 4.625 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.131 inches Maximum Pressure Rating: 2500.0 pounds per square inch Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spir	Metal winding w/ soft filler and outer ring
Outside Diameter: 2.719 inches Aperture Diameter: 1.875 inches Bearing Surface Width: 0.422 inches Bearing Surface Width: 0.422 inches Gage Ring Outside Diameter: 4.625 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.181 inches Maximum Pressure Rating: 2500.0 pounds per square inch Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm	Tempurature Rating:
2.719 inches Aperture Diameter: 1.875 inches Bearing Surface Width: 0.422 inches Gage Ring Outside Diameter: 4.625 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.131 inches Maximum Pressure Rating: 2500.0 pounds per square inch Material: Steel outer ring Material Specification: Millip-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and b class and ips11/2 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A032a0 Mil-std (military Standard):	900.0 degrees fahrenheit
Aperture Diameter: 1.875 inches Bearing Surface Width: 0.422 inches Gage Ring Outside Diameter: 4.625 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.170 inches and 0.131 inches Maximum Pressure Rating: 2500.0 pounds per square inch Material: Steel outer ring Material Specification: Mili-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and b class and ips11/2 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A03230 Mil-std (military Standard):	Outside Diameter:
1.875 inches Bearing Surface Width: 0.422 inches Gage Ring Outside Diameter: 4.625 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.131 inches Maximum Pressure Rating: 2500.0 pounds per square inch Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd astm b168 assn standard 2nd astm b168 assn standard 2nd	2.719 inches
Bearing Surface Width: 0.422 Inches Gage Ring Outside Diameter: 4.625 Inches Cross-sectional Thickness: Between 0.170 Inches and 0.180 Inches Gage Ring Thickness: Between 0.170 Inches and 0.131 Inches Maximum Pressure Rating: 2500.0 pounds per square inch Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and b class and ips11/2 size and 2500 series Shelf Life: N/a Unit Of Measure: ———————————————————————————————————	Aperture Diameter:
0.422 inches Gage Ring Outside Diameter: 4.625 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.181 inches Maximum Pressure Rating: 2500.0 pounds per square inch Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and b class and ips11/2 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	1.875 inches
Gage Ring Outside Diameter: 4.625 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 2500.0 pounds per square inch Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and b class and ips11/2 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Bearing Surface Width:
4.625 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 2500.0 pounds per square inch Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and b class and ips11/2 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig: A032a0 Mil-std (military Standard):	0.422 inches
Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 2500.0 pounds per square inch Material: Steel outer ring Material Specification: Mill-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and b class and ips11/2 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig: A032a0 Mill-std (military Standard):	Gage Ring Outside Diameter:
Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 2500.0 pounds per square inch Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler style Designator: Circular Specification Or Standard: 2 type and b class and ips11/2 size and 2500 series Shelf Life: Na Unit Of Measure: Demilitarization: No Filig: A032a0 Mil-std (military Standard):	4.625 inches
Gage Ring Thickness: Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 2500.0 pounds per square inch Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and b class and ips11/2 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Cross-sectional Thickness:
Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 2500.0 pounds per square inch Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral	Between 0.170 inches and 0.180 inches
Maximum Pressure Rating: 2500.0 pounds per square inch Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and b class and ips11/2 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Gage Ring Thickness:
2500.0 pounds per square inch Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and b class and ips11/2 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Between 0.117 inches and 0.131 inches
Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168	Maximum Pressure Rating:
Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and b class and ips11/2 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	2500.0 pounds per square inch
Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and b class and ips11/2 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Material:
Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and b class and ips11/2 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Steel outer ring
spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and b class and ips11/2 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Material Specification:
Style Designator: Circular Specification Or Standard: 2 type and b class and ips11/2 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response
Circular Specification Or Standard: 2 type and b class and ips11/2 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	spiral wound filler
Specification Or Standard: 2 type and b class and ips11/2 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Style Designator:
2 type and b class and ips11/2 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Circular
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Specification Or Standard:
N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	2 type and b class and ips11/2 size and 2500 series
Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Shelf Life:
Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	N/a
No Fiig: A032a0 Mil-std (military Standard):	Unit Of Measure:
No Fiig: A032a0 Mil-std (military Standard):	
Fiig: A032a0 Mil-std (military Standard):	Demilitarization:
A032a0 Mil-std (military Standard):	No
Mil-std (military Standard):	Fiig:
	A032a0
Mil-p-24503 spec.	Mil-std (military Standard):
	Mil-p-24503 spec.