NSN 5330-01-338-7785

Spiral Wound Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-01-338-7785

Metal winding w/ soft filler and outer ring	
Tompurature Patings	
Tempurature Rating:	
1050.0 degrees fahrenheit	
Outside Diameter:	
6.969 inches	
Aperture Diameter:	
5.812 inches	
Bearing Surface Width:	
0.579 inches	
Gage Ring Outside Diameter:	
10.000 inches	
Cross-sectional Thickness:	
Between 0.170 inches and 0.180 inches	
Gage Ring Thickness:	
Between 0.117 inches and 0.131 inches	
Maximum Pressure Rating:	
1500.0 pounds per square inch	
Environmental Attribute Code:	
Asbestos alternative products	
Material:	
Steel outer ring	
Material Specification:	
Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn spiral wound filler and astm a167 assn spiral wound filler and astm a167 assn spiral wound filler and a167 a	ponse
spiral wound filler	
Style Designator:	
Circular	
Specification Or Standard:	
2 type and a class and ips5 size and 1500 series	
Shelf Life:	
N/a	
Unit Of Measure:	
	
Demilitarization:	
No	
Fiig:	
A032a0	
Mil-std (military Standard):	
Mil-p-24503 spec.	