NSN 5330-01-338-7791

Spiral Wound Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-01-338-7791

Metal winding w/ soft filler and outer ring Tempurature Rating: 10.00 degrees fabrenheit Outside Diameter: 12.469 inches Aperture Diameter: 12.469 inches Bearing Surface Width: 0.579 inches Bearing Surface Width: 0.579 inches Gage Ring Outside Diameter: 13.375 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.170 inches and 0.181 inches Maximum Pressure Rating: 150.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material Specification: Mili-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response Sheff Life: Na Utili Of Measure:	
Tempurature Rating: 1050.0 degrees fahrenheit Outside Diameter: 12.469 inches Aperture Diameter: 11.312 inches Bearing Surface Width: 0.579 inches Gage Ring Outside Diameter: 13.375 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.170 inches and 0.131 inches Maximum Pressure Rating: 150.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mili-p-24503, type 1, ol 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and a standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips10 size and 150 series Shelf Life: No Unit Of Measure: — Demilitarization: No Filig: 403230 Mili-std (military Standard):	Cross Sectional Shape:
1050.0 degrees fahrenheit Outside Diameter: 12.469 inches Apperture Diameter: 11.312 inches Bearing Surface Width: 0.579 inches Gage Ring Outside Diameter: 13.375 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.131 inches Maximum Pressure Rating: 160.0 pounds per square inch Environmental Attribute Code: Aabeatos alternative products Material: Steel outer ring Material: Steel outer ring Material Specification: Whit-p-24503, type 1, ol 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a169 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound fille	Metal winding w/ soft filler and outer ring
Outside Diameter: 12.469 inches Aperture Diameter: 11.312 inches Bearing Surface Width: 0.579 inches Gage Ring Outside Diameter: 13.375 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.170 inches and 0.181 inches Maximum Pressure Rating: 150.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response Spiral wound filler and astm a167 assn standard 2nd material response Spiral wound filler and astm a167 assn standard 2nd material response Spiral wound filler and astm a167 assn standard 2nd material response Spiral wound filler and astm a167 assn standard 2nd material response Spiral wound filler and astm a167 assn standard 2nd material response Spiral wound filler and astm a167 assn standard 2nd material response Spiral wound filler and astm a167 assn standard 2nd material response Spiral wound filler and astm a167 assn standard 2nd material response Spiral wound filler and astm a167 assn standard 2nd material response Spiral wound filler and astm a167 assn standard 2nd material response Spiral wound filler and astm a167 assn standard 2nd material response Spiral wound filler and astm a167 assn standard 2nd material response Spiral wound filler and astm a167 assn standard 2nd material response Spiral wound filler and astm a167 assn standard 2nd material response Spiral wound filler and astm a167 assn standard 2nd material response Spiral wound filler and astm a167 assn standard 2nd material response Spiral wound filler and astm a167 assn standard 2nd material response Spiral wound filler and astm a167 assn standard 2nd material response Spi	Tempurature Rating:
12.469 inches Aperture Diameter: 11.312 inches Bearing Surface Width: 0.579 inches Gage Ring Outside Diameter: 13.375 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.170 inches and 0.181 inches Maximum Pressure Rating: 150.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Siteel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd astm a167 assn standard 2nd astm a167	1050.0 degrees fahrenheit
Aperture Diameter: 11.312 inches Bearing Surfaco Width: 0.579 inches Gage Ring Outside Diameter: 13.375 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.181 inches Maximum Pressure Rating: 150.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material: Steel outer ring Material Specification: Mit-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips10 size and 150 series Shelf Life: No Unit Of Measure: — Demilitarization: No Filig: A032a0 Mili-std (military Standard):	Outside Diameter:
11.312 inches Bearing Surface Width: 0.579 inches Gage Ring Outside Diameter: 13.375 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.131 inches Maximum Pressure Rating: 150.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips10 size and 150 series Shelf Life: No Unit Of Measure: — Demilitarization: No Fifig: A032a0 Mil-std (military Standard):	12.469 inches
Bearing Surface Wildth: 0.579 inches Gage Ring Outside Diameter: 13.375 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.181 inches Maximum Pressure Rating: 150.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material: Steel outer ring Material Specification: Mili-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips10 size and 150 series Shelf Life: No Unit Of Measure: — Demilitarization: No Fifig: A032a0 Mil-std (military Standard):	Aperture Diameter:
0.579 inches Gage Ring Outside Diameter: 13.375 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.131 inches Maximum Pressure Rating: 150.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips10 size and 150 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig: A032a0 Mil-std (military Standard):	11.312 inches
Gage Ring Outside Diameter: 13.375 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.131 inches Maximum Pressure Rating: 150.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips10 size and 150 series Shelf Life: N/a Unit Of Measure: ———————————————————————————————————	Bearing Surface Width:
13.375 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 150.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mili-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips10 size and 150 series Shelf Life: N/a Unit Of Measure: ———————————————————————————————————	0.579 inches
Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 150.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips10 size and 150 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A03230 Mil-std (military Standard):	Gage Ring Outside Diameter:
Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 150.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd astm a167 assn standard 2nd astm a167 assn sta	13.375 inches
Gage Ring Thickness: Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 150.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material respon	Cross-sectional Thickness:
Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 150.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler style Designator: Circular Style Designator: Circular Specification Or Standard: 2 type and a class and ips10 size and 150 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Between 0.170 inches and 0.180 inches
Maximum Pressure Rating: 150.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips10 size and 150 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A032a0 Mill-std (military Standard):	Gage Ring Thickness:
150.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound	Between 0.117 inches and 0.131 inches
Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mili-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips10 size and 150 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mili-std (military Standard):	Maximum Pressure Rating:
Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips10 size and 150 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	150.0 pounds per square inch
Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler style Designator: Circular Specification Or Standard: 2 type and a class and ips10 size and 150 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Environmental Attribute Code:
Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler style Designator: Circular Specification Or Standard: 2 type and a class and ips10 size and 150 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Asbestos alternative products
Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips10 size and 150 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Material:
Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips10 size and 150 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Steel outer ring
spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips10 size and 150 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Material Specification:
Style Designator: Circular Specification Or Standard: 2 type and a class and ips10 size and 150 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response
Circular Specification Or Standard: 2 type and a class and ips10 size and 150 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A032a0 Mil-std (military Standard):	spiral wound filler
Specification Or Standard: 2 type and a class and ips10 size and 150 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Style Designator:
2 type and a class and ips10 size and 150 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Circular
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Specification Or Standard:
N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	2 type and a class and ips10 size and 150 series
Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Shelf Life:
Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	N/a
Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Unit Of Measure:
No Fiig: A032a0 Mil-std (military Standard):	
Fiig: A032a0 Mil-std (military Standard):	Demilitarization:
A032a0 Mil-std (military Standard):	No
Mil-std (military Standard):	Fiig:
	A032a0
Mil-p-24503 spec.	Mil-std (military Standard):
	Mil-p-24503 spec.