NSN 5330-01-338-7795

Spiral Wound Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-01-338-7795

| Tempurature Rating: | |
|---|--------|
| Tempurature Rating: | |
| | |
| 1050.0 degrees fahrenheit | |
| Outside Diameter: | |
| 12.469 inches | |
| Aperture Diameter: | |
| 10.812 inches | |
| Bearing Surface Width: | |
| 0.829 inches | |
| Gage Ring Outside Diameter: | |
| 15.750 inches | |
| Cross-sectional Thickness: | |
| Between 0.170 inches and 0.180 inches | |
| Gage Ring Thickness: | |
| Between 0.117 inches and 0.131 inches | |
| Maximum Pressure Rating: | |
| 600.0 pounds per square inch | |
| Environmental Attribute Code: | |
| Asbestos alternative products | |
| Material: | |
| Steel outer ring | |
| Material Specification: | |
| Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material res | sponse |
| spiral wound filler | |
| Style Designator: | |
| Circular | |
| Specification Or Standard: | |
| 2 type and a class and ips10 size and 600 series | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A032a0 | |
| Mil-std (military Standard): | |
| Mil-p-24503 spec. | |