NSN 5330-01-338-7804

Spiral Wound Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-01-338-7804

Metal winding w/ soft filler and outer ring Tempurature Rating: 700.0 degrees fahrenheit Dutside Diameter: 2.344 inches Aperture Diameter: 2.345 inches Bearing Surface Width: 3.328 inches Beareng Outside Diameter: 3.329 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Bearen 0.170 inches and 0.181 inches Maximum Pressure Rating: 500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mili-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Style Designator: Director Dire	
Tempurature Rating: 700.0 degrees fahrenheit 7	Cross Sectional Shape:
700.0 degrees fahrenheit Dutside Diameter: 2.344 inches Aperture Diameter: 1.688 inches 3earing Surface Width: 3.28 inches 3earing Surface Width: 3.280 inches 3earing Thickness: 2.590 inches Cross-sectional Thickness: 2.69tween 0.170 inches and 0.180 inches 3eage Ring Thickness: 2.69tween 0.177 inches and 0.131 inches Maximum Pressure Rating: 300.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: 2.69te Journal of Products Material: 2.69te Journal of Products Milep-24503, type 1; 0.12 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler or gq-n-281, cl a federal specification 2nd material response spiral wound filler or gq-n-281, cl a federal specification 2nd material response spiral wound filler or gq-n-281, cl a federal specification 2nd material response spiral wound filler or gq-n-281, cl a federal specification 2nd material response spiral wound filler or gq-n-281, cl a federal specification 2nd material response spiral wound filler or gq-n-281, cl a federal specification 2nd material response spiral wound filler or gq-n-281, cl a federal specification 2nd material response spiral wound filler or gq-n-281, cl a federal specification 2nd material response spiral wound filler or gq-n-281, cl a federal specification 2nd material response spiral wound filler or gq-n-281, cl a federal specification 2nd material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler and astm b127 assn standard 2nd material response spir	Metal winding w/ soft filler and outer ring
Custide Diameter: 2.344 inches Aperture Diameter: 1.688 inches Bearing Surface Width: 2.328 inches Bearing Surface Width: 2.328 inches Bage Ring Outside Diameter: 3.250 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Bage Ring Thickness: Between 0.171 inches and 0.131 inches Maximum Pressure Rating: 300.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Stele outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and c class or ips11/4 size and 600 series Shelf Life: Wa Unit Of Measure:	Tempurature Rating:
Aperture Diameter: 1.688 inches Bearing Surface Width: 3.250 inches Gage Ring Outside Diameter: 3.250 inches Gross-sectional Thickness: 3.etween 0.170 inches and 0.180 inches Sage Ring Thickness: 3.etween 0.170 inches and 0.181 inches Maximum Pressure Rating: 300.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Specification: Circular Specification Or Standard: 2 type and c class or ips11/4 size and 600 series Shelf Life: Via Unit Of Measure: — Demilitarization: No Filigie 100.032a0 Will-std (military Standard):	700.0 degrees fahrenheit
Aperture Diameter: 1.688 inches 3earing Surface Width: 2.328 inches 3earing Surface Width: 2.328 inches 3earing Outside Diameter: 3.250 inches and 0.180 inches 3.250 inches and 0.181 inches	Outside Diameter:
Bearing Surface Width:	2.344 inches
Bearing Surface Width:	Aperture Diameter:
Daze Ring Outside Diameter: 3.250 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Bage Ring Thickness: Between 0.171 inches and 0.181 inches Maximum Pressure Rating: 300.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Wil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and c class or ips11/4 size and 600 series Shelf Life: Wil- Dimilitarization: No Dimilitarization: Domilitarization: Mil-p-24503 (mil-std (military Standard):	1.688 inches
Sage Ring Outside Diameter: 3.250 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.131 inches Maximum Pressure Rating: 300.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Wil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler and castm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and c class or ips11/4 size and 600 series Shelf Life: Wa Unit Of Measure:	Bearing Surface Width:
2.250 inches Cross-sectional Thickness: 3etween 0.170 inches and 0.180 inches 3age Ring Thickness: 3etween 0.117 inches and 0.131 inches 4aximum Pressure Rating: 300.0 pounds per square inch 5ervironmental Attribute Code: 4axisestos alternative products 4aximum Pressure Rating: 5teel outer ring 4aterial: Steel outer ring 4aterial Specification: Wil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or q-n-281, cl a federal specification 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and c class or ips11/4 size and 600 series Shelf Life: V/a Unit Of Measure:	0.328 inches
Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.117 inches and 0.131 inches Maximum Pressure Rating: Boo.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Wil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and c class or ips11/4 size and 600 series Shelf Life: Wa Unit Of Measure: Demilitarization: No Filig: A032a0 Wil-std (military Standard):	Gage Ring Outside Diameter:
Setween 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 300.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mit-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and c class or ips11/4 size and 600 series Shelf Life: Wa Unit Of Measure: Demilitarization: No Filig: A032a0 Will-std (military Standard):	3.250 inches
Sage Ring Thickness: Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Will-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and c class or ips11/4 size and 600 series Shelf Life: W/a Unit Of Measure: Demilitarization: No Filig: A032a0 Will-std (military Standard):	Cross-sectional Thickness:
Maximum Pressure Rating: 300.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and c class or ips11/4 size and 600 series Shelf Life: W/a Unit Of Measure: Demilitarization: No Filig: A03200 Mil-std (military Standard):	Between 0.170 inches and 0.180 inches
Maximum Pressure Rating: 500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and c class or ips11/4 size and 600 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A032a0 Will-std (military Standard):	Gage Ring Thickness:
Solution pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and c class or ips11/4 size and 600 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A032a0 Will-std (military Standard):	Between 0.117 inches and 0.131 inches
Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Will-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and c class or ips11/4 size and 600 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A032a0 Wil-std (military Standard):	Maximum Pressure Rating:
Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and c class or ips11/4 size and 600 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A032a0 Wil-std (military Standard):	600.0 pounds per square inch
Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and c class or ips11/4 size and 600 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A032a0 Mil-std (military Standard):	Environmental Attribute Code:
Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and c class or ips11/4 size and 600 series Shelf Life: Wa Unit Of Measure: Demilitarization: No Filig: 4032a0 Will-std (military Standard):	Asbestos alternative products
Material Specification: Wil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and c class or ips11/4 size and 600 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Wil-std (military Standard):	Material:
Wil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and c class or ips11/4 size and 600 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Wil-std (military Standard):	Steel outer ring
Style Designator: Circular Specification Or Standard: 2 type and c class or ips11/4 size and 600 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A032a0 Will-std (military Standard):	Material Specification:
Style Designator: Circular Specification Or Standard: 2 type and c class or ips11/4 size and 600 series Shelf Life: Wa Unit Of Measure: Demilitarization: No Fiig: A032a0 Will-std (military Standard):	Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response
Circular Specification Or Standard: 2 type and c class or ips11/4 size and 600 series Shelf Life: V/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler
Specification Or Standard: 2 type and c class or ips11/4 size and 600 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Style Designator:
2 type and c class or ips11/4 size and 600 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Circular
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Specification Or Standard:
Voit Of Measure:	2 type and c class or ips11/4 size and 600 series
Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Shelf Life:
Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	N/a
No Fiig: A032a0 Mil-std (military Standard):	Unit Of Measure:
No Fiig: A032a0 Mil-std (military Standard):	
Fiig: 4032a0 Mil-std (military Standard):	Demilitarization:
A032a0 Mil-std (military Standard):	No
Mil-std (military Standard):	Fiig:
	A032a0
Mil-n-24503 snec	Mil-std (military Standard):
νιιτρταπούο όρφο.	Mil-p-24503 spec.