NSN 5330-01-338-7815

Spiral Wound Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-01-338-7815

Metal winding w' soft filler and outer ring Tompurture Rating: 1050.0 degrees fahrenheit Outside Diameter: 3.344 inches Aperture Diameter: 2.342 inches Bearing Surface Width: 0.518 inches Bearing Surface Width: 0.518 inches Gage Ring Outside Diameter: 5.750 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.131 inches Maximum Pressure Rating: 2500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mili-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response Sheff Life: Na Unit Of Measure:	
Tempurature Rating: 1050.0 degrees fahrenheit Outside Diameter: 3.344 inches Aperture Diameter: 2.312 inches Bearing Surface Width: 0.516 inches Gage Ring Outside Diameter: 5.750 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.170 inches and 0.181 inches Maximum Pressure Rating: 2500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Stoel outer ring Material Specification: Miti-p-24503, type 1, ol 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and active acti	Cross Sectional Shape:
1050.0 degrees fahrenheit Outside Diameter: 3.344 inches Aperture Diameter: 2.312 inches Bearing Surface Width: 0.516 inches Gage Ring Outside Diameter: 5.750 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.131 inches Maximum Pressure Rating: 2500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, ol 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2	Metal winding w/ soft filler and outer ring
Outside Diameter: 3.344 inches Aperture Diameter: 2.312 inches Bearing Surface Width: 0.518 inches Bearing Surface Width: 0.518 inches Gage Ring Outside Diameter: 5.750 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.131 inches Maximum Pressure Rating: 2500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response and a187 assn standard 2	Tempurature Rating:
3.344 inches Aperture Diameter: 2.312 inches Bearing Surface Width: 0.516 inches Gage Ring Outside Diameter: 5.750 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.170 inches and 0.181 inches Maximum Pressure Rating: 2500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24603, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Syle Designator: Circular Specification Or Standard: 2 type and a class and ips2 size and 2500 series Shelf Life: N/a Unit Of Measure: — Demilitarization: No Fifig: A032a0 Mil-std (military Standard):	1050.0 degrees fahrenheit
Aperture Diameter: 2.312 inches Bearing Surface Width: 0.516 inches Gage Ring Outside Diameter: 5.750 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.181 inches Maximum Pressure Rating: 2500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mili-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response approach as a spiral wound filler and astm a167 assn standard 2nd material response approach as a spiral wound filler and astm a167 assn standard 2nd material response approach as a spiral wound filler and astm a167 assn standard 2nd material response approach as a spiral wound filler and astm a167 assn standard 2nd material response approach as a spiral wound filler and astm a167 assn standard 2nd material response approach as a spiral wound filler a	Outside Diameter:
2.312 inches Bearing Surface Width: 0.516 inches Gage Ring Outside Diameter: 5.750 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.131 inches Maximum Pressure Rating: 2500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mili-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips2 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A03240 Mil-std (military Standard):	3.344 inches
Bearing Surface Width: 0.516 inches Gage Ring Outside Diameter: 5.750 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.181 inches Maximum Pressure Rating: 2500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material: Steel outer ring Material Specification: Mili-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips2 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A03240 Mil-std (military Standard):	Aperture Diameter:
0.516 inches Gage Ring Outside Diameter: 5.750 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.131 inches Maximum Pressure Rating: 2500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips2 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig: A032a0 Mil-std (military Standard):	2.312 inches
Gage Ring Outside Diameter: 5.750 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.131 inches Maximum Pressure Rating: 2500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response Style Designator: Circular Specification Or Standard: 2 type and a class and ips2 size and 2500 series Shelf Life: N/a Unit Of Measure: ————————————————————————————————————	Bearing Surface Width:
5.750 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 2500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd and	0.516 inches
Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 2500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips2 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig: A032a0 Mil-std (military Standard):	Gage Ring Outside Diameter:
Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 2500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and ast	5.750 inches
Gage Ring Thickness: Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 2500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response	Cross-sectional Thickness:
Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 2500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Style Designator: Circular Specification Or Standard: 2 type and a class and ips2 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Between 0.170 inches and 0.180 inches
Maximum Pressure Rating: 2500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips2 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Gage Ring Thickness:
2500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral woun	Between 0.117 inches and 0.131 inches
Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn stan	Maximum Pressure Rating:
Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips2 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	2500.0 pounds per square inch
Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167	Environmental Attribute Code:
Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips2 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Asbestos alternative products
Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips2 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Material:
Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips2 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Steel outer ring
spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips2 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Material Specification:
Style Designator: Circular Specification Or Standard: 2 type and a class and ips2 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response
Circular Specification Or Standard: 2 type and a class and ips2 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	spiral wound filler
Specification Or Standard: 2 type and a class and ips2 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Style Designator:
2 type and a class and ips2 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Circular
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Specification Or Standard:
N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	2 type and a class and ips2 size and 2500 series
Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Shelf Life:
Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	N/a
No Fiig: A032a0 Mil-std (military Standard):	Unit Of Measure:
No Fiig: A032a0 Mil-std (military Standard):	
Fiig: A032a0 Mil-std (military Standard):	Demilitarization:
A032a0 Mil-std (military Standard):	No
Mil-std (military Standard):	Fiig:
	A032a0
Mil-p-24503 spec.	Mil-std (military Standard):
	Mil-p-24503 spec.