NSN 5330-01-338-7826

Spiral Wound Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-01-338-7826

spiral wound filler Style Designator: Circular Specification Or Standard: 600 series and 3.000 size Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	
Tempurature Rating: 200.0 degrees fahrenheit Outside Diameter: 4.719 inches Aperture Diameter: 3.750 inches Bearing Surface Width: 0.485 inches Gage Ring Outside Diameter: 5.875 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.131 inches Maximum Pressure Rating: 800.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mili-p-24503, type 1, ol 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and 3.000 size Shelf Life: We Unit Of Measure:	Cross Sectional Shape:
300.0 degrees fahrenheit Outside Diameter: 4.719 inches Apperture Diameter: 3.750 inches Bearing Surface Width: 0.485 inches Gage Ring Outside Diameter: 5.875 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.1717 inches and 0.131 inches Maximum Pressure Rating: 600.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Whit-p-24503, type 1, ol 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and 3.000 size Shelf Life: Na Unit of Measure:	Metal winding w/ soft filler and outer ring
Outside Diameter: 4.719 inches Aperture Diameter: 3.750 inches Bearing Surface Width: 0.485 inches Bearing Surface Width: 0.485 inches Gage Ring Outside Diameter: 5.875 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.170 inches and 0.131 inches Maximum Pressure Rating: 800.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 600 series and 3.000 size Shelf Life: No Unit of Measure: ————————————————————————————————————	Tempurature Rating:
4.719 inches Aperture Diameter: 3.750 inches Bearing Surface Width: 0.485 inches Gage Ring Outside Diameter: 5.875 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.170 inches and 0.181 inches Maximum Pressure Rating: 800.0 pounds per square inch Environmental Attribute Code: Abbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and	900.0 degrees fahrenheit
Aperture Diameter: 3.750 inches Bearing Surface Width: 0.485 inches Gage Ring Outside Diameter: 5.875 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.181 inches Maximum Pressure Rating: Between 0.171 inches and 0.181 inches Maximum Pressure Rating: Between 0.175 inches and 0.181 inches Maximum Pressure Rating: Between 0.175 inches and 0.181 inches Maximum Pressure Rating: Between 0.176 inches and 0.181 inches Maximum Pressure Rating: Between 0.176 inches and 0.181 inches Maximum Pressure Rating: Between 0.176 inches and 0.181 inches Maximum Pressure Rating: Between 0.176 inches and 0.181 inches Maximum Pressure Rating: Between 0.176 inches and 0.181 inches Maximum Pressure Rating: Between 0.176 inches and 0.181 inches Maximum Pressure Rating: Between 0.176 inches and 0.181 inches Maximum Pressure Rating: Between 0.176 inches and 0.181 inches Maximum Pressure Rating: Between 0.176 inches and 0.181 inches Maximum Pressure Rating: Between 0.176 inches and 0.180 inches Mile-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound f	Outside Diameter:
Bearing Surface Width: 0.485 inches Gage Ring Outside Diameter: 5.875 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.181 inches Maximum Pressure Rating: 600.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 600 series and 3.000 size Shelf Life: No Unit Of Measure: — Demilitarization: No Fig: A032a0 Mil-std (military Standard):	4.719 inches
Bearing Surface Width: 0.485 inches Gage Ring Outside Diameter: 5.875 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.177 inches and 0.181 inches Maximum Pressure Rating: 600.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 600 series and 3.000 size Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig: A03230 Mil-std (military Standard):	Aperture Diameter:
0.485 inches Gage Ring Outside Diameter: 5.875 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.131 inches Maximum Pressure Rating: 600.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 600 series and 3.000 size Shelf Life: N/a Unit Of Measure: — Demilitarization: No Fifig: A032a0 Mil-std (military Standard):	3.750 inches
Gage Ring Outside Diameter: 5.875 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.131 inches Maximum Pressure Rating: 600.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and a	Bearing Surface Width:
5.875 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 600.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 600 series and 3.000 size Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A032a0 Mil-std (military Standard):	0.485 inches
Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 800.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 800 series and 3.000 size Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig: A03230 Mil-std (military Standard):	Gage Ring Outside Diameter:
Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 600.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 600 series and 3.000 size Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	5.875 inches
Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 600.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler solven as and 3.000 size Style Designator: Circular Specification Or Standard: 600 series and 3.000 size Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A032a0 Mil-std (military Standard):	Cross-sectional Thickness:
Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 600.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler style Designator: Circular Style Designator: Circular Specification Or Standard: 600 series and 3.000 size Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Between 0.170 inches and 0.180 inches
Maximum Pressure Rating: 600.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 600 series and 3.000 size Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Gage Ring Thickness:
Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 600 series and 3.000 size Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A032a0 Mil-std (military Standard):	Between 0.117 inches and 0.131 inches
Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn stan	Maximum Pressure Rating:
Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response sp	600.0 pounds per square inch
Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 600 series and 3.000 size Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Environmental Attribute Code:
Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler and astm b168 assn standard 2nd material	Asbestos alternative products
Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 600 series and 3.000 size Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Material:
Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler Style Designator: Circular Specification Or Standard: 600 series and 3.000 size Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Steel outer ring
spiral wound filler Style Designator: Circular Specification Or Standard: 600 series and 3.000 size Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Material Specification:
Style Designator: Circular Specification Or Standard: 600 series and 3.000 size Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response
Circular Specification Or Standard: 600 series and 3.000 size Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	spiral wound filler
Specification Or Standard: 600 series and 3.000 size Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Style Designator:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Circular
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Specification Or Standard:
N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	600 series and 3.000 size
Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Shelf Life:
Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	N/a
No Fiig: A032a0 Mil-std (military Standard):	Unit Of Measure:
No Fiig: A032a0 Mil-std (military Standard):	
Fiig: A032a0 Mil-std (military Standard):	Demilitarization:
A032a0 Mil-std (military Standard):	No
Mil-std (military Standard):	Fiig:
	A032a0
	Mil-std (military Standard):
Mil-p-24503 spec.	Mil-p-24503 spec.