NSN 5330-01-338-7832

Spiral Wound Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-01-338-7832

Metal winding w/ soft filler and outer ring Tompurature Rating: 1.219 inches Aperture Diameter: 1.219 inches Aperture Diameter: 0.750 inches Bearing Surface Width: 0.235 inches Bearing Surface Width: 0.235 inches Gage Ring Outside Diameter: 2.500 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.170 inches and 0.181 inches Maximum Pressure Rating: 1500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Sleel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response Shelf Life: Na Unit of Measure: Demilitarization: No Filig: A03320 Mil-std (military Standard):	
Tempurature Rating: 105.0.0 degrees fahrenheit Outside Diameter: 1.219 inches Aperture Diameter: 0.750 inches Bearing Surface Width: 0.750 inches Bearing Surface Width: 0.750 inches Gage Ring Outside Diameter: 2.500 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.170 inches and 0.131 inches Maximum Pressure Rating: 1500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Siteel outer ring Material Specification: Mit-p-2460s, type 1, d. 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and active and act	Cross Sectional Shape:
1050.0 degrees fahrenheit Outside Diameter: 1.219 inches Aperture Diameter: 0.750 inches Bearing Surface Width: 0.235 inches Gage Ring Outside Diameter: 2.500 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.170 inches and 0.181 inches Maximum Pressure Rating: 1500.0 pounds per square inch Environmental Attribute Code: Abbestos alternative products Material: Steel outer ring Miterial Specification: Miterial Specification or Standard: Style Designator: Circular Specification or Standard: 2 type and a class and ips1/2 size and 1500 series Shelf Life: Na Unit of Measure: Demilitarization: No Filig: A03280 Mil-std (military Standard):	Metal winding w/ soft filler and outer ring
Outside Diameter: 1.219 inches Aperture Diameter: 0.750 inches Bearing Surface Width: 0.235 inches Bearing Surface Width: 0.235 inches Gage Ring Outside Diameter: 2.500 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.170 inches and 0.131 inches Maximum Pressure Rating: 1500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response and a167 assn standard 2	Tempurature Rating:
Aperture Diameter: 0.750 inches Bearing Surface Width: 0.253 inches Gage Ring Outside Diameter: 2.500 inches Gage Ring Outside Diameter: 2.500 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.170 inches and 0.181 inches Maximum Pressure Rating: 1500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mit-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd astm a167 ass	1050.0 degrees fahrenheit
Aperture Diameter: 0.750 inches Bearing Surface Width: 0.235 inches Gage Ring Outside Diameter: 2.500 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.181 inches Maximum Pressure Rating: 1500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Sylve Designator: Circular Specification Or Standard: 2 type and a class and ips1/2 size and 1500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A032a0 Mil-std (military Standard):	Outside Diameter:
Bearing Surface Width: 0.25 inches Gage Ring Outside Diameter: 2.500 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.181 inches Maximum Pressure Rating: 1500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips1/2 size and 1500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A032a0 Mil-std (military Standard):	1.219 inches
Bearing Surface Width: 0.235 inches Gage Ring Outside Diameter: 2.500 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.181 inches Maximum Pressure Rating: 1500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material: Steel outer ring Material Specification: Milli-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips1/2 size and 1500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A032a0 Mil-std (military Standard):	Aperture Diameter:
0.235 inches Gage Ring Outside Diameter: 2.500 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.131 inches Maximum Pressure Rating: 1500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips1/2 size and 1500 series Shelf Life: Na Unit Of Measure: Demilitarization: No Fifig: A032a0 Mil-std (military Standard):	0.750 inches
Gage Ring Outside Diameter: 2.500 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.131 inches Maximum Pressure Rating: 1500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and ast	Bearing Surface Width:
2.500 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 1500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler on a standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips1/2 size and 1500 series Shelf Life: N/a Unit Of Measure: ———————————————————————————————————	0.235 inches
Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 1500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips1/2 size and 1500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig: A032a0 Mil-std (military Standard):	Gage Ring Outside Diameter:
Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 1500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and ast	2.500 inches
Gage Ring Thickness: Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 1500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response	Cross-sectional Thickness:
Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 1500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips1/2 size and 1500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Between 0.170 inches and 0.180 inches
Maximum Pressure Rating: 1500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips1/2 size and 1500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig: A032a0 Mil-std (military Standard):	Gage Ring Thickness:
1500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral woun	Between 0.117 inches and 0.131 inches
Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn stan	Maximum Pressure Rating:
Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips1/2 size and 1500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	1500.0 pounds per square inch
Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167	Environmental Attribute Code:
Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips1/2 size and 1500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Asbestos alternative products
Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips1/2 size and 1500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Material:
Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips1/2 size and 1500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Steel outer ring
spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips1/2 size and 1500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Material Specification:
Style Designator: Circular Specification Or Standard: 2 type and a class and ips1/2 size and 1500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response
Circular Specification Or Standard: 2 type and a class and ips1/2 size and 1500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	spiral wound filler
Specification Or Standard: 2 type and a class and ips1/2 size and 1500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Style Designator:
2 type and a class and ips1/2 size and 1500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Circular
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Specification Or Standard:
N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	2 type and a class and ips1/2 size and 1500 series
Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Shelf Life:
Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	N/a
No Fiig: A032a0 Mil-std (military Standard):	Unit Of Measure:
No Fiig: A032a0 Mil-std (military Standard):	
Fiig: A032a0 Mil-std (military Standard):	Demilitarization:
A032a0 Mil-std (military Standard):	No
Mil-std (military Standard):	Fiig:
	A032a0
Mil-p-24503 spec.	Mil-std (military Standard):
	Mil-p-24503 spec.