## NSN 5330-01-338-7855

Spiral Wound Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-01-338-7855

| Cross Sectional Shape:   |
|--|
| Metal winding w/ soft filler and outer ring  |
| Tempurature Rating:  |
| 700.0 degrees fahrenheit   |
| Outside Diameter:  |
| 3.844 inches   |
| Aperture Diameter:   |
| 3.125 inches   |
| Bearing Surface Width:   |
| 0.360 inches   |
| Gage Ring Outside Diameter:  |
| 4.875 inches   |
| Cross-sectional Thickness:   |
| Between 0.170 inches and 0.180 inches  |
| Gage Ring Thickness:   |
| Between 0.117 inches and 0.131 inches  |
| Maximum Pressure Rating:   |
| 150.0 pounds per square inch   |
| Environmental Attribute Code:  |
| Asbestos alternative products  |
| Material:  |
| Steel outer ring   |
| Material Specification:  |
| Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response |
| spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler  |
| Style Designator:  |
| Circular   |
| Specification Or Standard:   |
| 2 type and c class and ips21/2 size and 150 series   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A032a0   |
| Mil-std (military Standard):   |
| Mil-p-24503 spec.  |
|  |