NSN 5330-01-338-7866

Spiral Wound Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-01-338-7866

| Cross Sectional Shape: |
|--|
| Metal winding w/ soft filler and outer ring |
| Tempurature Rating: |
| 1050.0 degrees fahrenheit |
| Outside Diameter: |
| 10.344 inches |
| Aperture Diameter: |
| 3.875 inches |
| Bearing Surface Width: |
| 0.735 inches |
| Gage Ring Outside Diameter: |
| 12.000 inches |
| Cross-sectional Thickness: |
| Between 0.170 inches and 0.180 inches |
| Gage Ring Thickness: |
| Between 0.117 inches and 0.131 inches |
| Maximum Pressure Rating: |
| 400.0 pounds per square inch |
| Environmental Attribute Code: |
| Asbestos alternative products |
| Material: |
| Steel outer ring |
| Material Specification: |
| Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response |
| spiral wound filler |
| Style Designator: |
| Circular |
| Specification Or Standard: |
| 2 type and a class and ips8 size and 400 series |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Filg: |
| A032a0 |
| Mil-std (military Standard): |
| Mil-p-24503 spec. |
| |