## NSN 5330-01-338-7871

Spiral Wound Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-01-338-7871

Metal winding w/ soft filler and outer ring Tempurature Rating: 10.105.0.0 degrees fahrenheit Outside Diameter: 14.719 inches Aperture Diameter: 14.719 inches Bearing Surface Width: 0.922 inches Bearing Surface Width: 0.922 inches Gage Ring Outside Diameter: 20.500 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.170 inches and 0.131 inches Maximum Pressure Rating: 1500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mili-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips12 size and 1500 series Shelf Life: No Unit Of Measure:	
Tempurature Rating: 1050.0 degrees fahrenheit Outside Diameter: 14.719 inches Aperture Diameter: 12.875 inches Bearing Surface Width: 0.922 inches Gage Ring Outside Diameter: 20.500 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.131 inches Maximum Pressure Rating: 1500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mili-p-24503, type 1, ol 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and action action of Students Specification Or Standard: 2 type and a class and ips12 size and 1500 series Shell Life: No Unit Of Measure: — Demilitarization: No Filig: 403230 Mili-std (military Standard):	Cross Sectional Shape:
1050.0 degrees fahrenheit Outside Diameter: 14.719 inches Apperture Diameter: 12.875 inches Bearing Surface Width: 0.922 inches Gage Ring Outside Diameter: 20.500 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.131 inches Maximum Pressure Rating: 1500.0 pounds per square inch Environmental Attribute Code: Aabeatos alternative products Material: Steel outer ring Material: Steel outer ring Material Specification: Whit-p-24503, type 1, ol 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and a standard 2	Metal winding w/ soft filler and outer ring
Outside Diameter: 14.719 inches Aperture Diameter: 14.875 inches Bearing Surface Width: 0.922 inches Gage Ring Outside Diameter: 20.500 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.170 inches and 0.181 inches Maximum Pressure Rating: 1500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response Spiral wound filler and astm a167 assn standard 2nd material response Spiral wound filler and astm a167 assn standard 2nd material response Spiral wound filler and astm a167 assn standard 2nd material response Spiral wound filler and astm a167 assn standard 2nd material response Spiral wound filler and astm a167 assn standard 2nd material response Spiral wound filler and astm a167 assn standard 2nd material response Spiral wound filler and astm a167 assn standard 2nd material response Spiral wound filler and astm a167 assn standard 2nd material response Spiral wound filler and astm a167 assn standard 2nd material response Spiral wound filler and astm a167 assn standard 2nd material response Spiral wound filler and astm a167 assn standard 2nd material response Spiral wound filler and astm a167 assn standard 2nd material response Spiral wound filler and astm a167 assn standard 2nd material response Spiral wound filler and astm a167 assn standard 2nd material response Spiral wound filler and astm a167 assn standard 2nd material response Spiral wound filler and astm a167 assn standard 2nd material response Spiral wound filler and astm a167 assn standard 2nd material response Spiral wound filler and astm a167 assn standard 2nd material response Sp	Tempurature Rating:
14.719 inches Aperture Diameter: 12.875 inches Bearing Surface Width: 0.922 inches Gage Ring Outside Diameter: 20.500 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.170 inches and 0.181 inches Maximum Pressure Rating: 1500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Siteel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd astm a167 assn standard 2nd astm a167	1050.0 degrees fahrenheit
Aperture Diameter:  12.875 inches  Bearing Surfaco Width:  0.922 inches  Gage Ring Outside Diameter:  20.500 inches  Cross-sectional Thickness:  Between 0.170 inches and 0.180 inches  Gage Ring Thickness:  Between 0.171 inches and 0.181 inches  Maximum Pressure Rating:  1500.0 pounds per square inch  Environmental Attribute Code:  Asbestos alternative products  Material:  Steel outer ring  Material Specification:  Mit-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler  Style Designator:  Circular  Specification Or Standard:  2 type and a class and ips12 size and 1500 series  Shelf Life:  No  Unit Of Measure:  —  Demilitarization:  No  Filig:  A032a0  Mili-std (military Standard):	Outside Diameter:
12.875 inches Bearing Surface Width: 0.922 inches Gage Ring Outside Diameter: 20.500 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.131 inches Maximum Pressure Rating: 1500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips12 size and 1500 series Shelf Life: No Unit Of Measure: — Demilitarization: No Fifig: A032a0 Mil-std (military Standard):	14.719 inches
Bearing Surface Wildth:  0.922 inches Gage Ring Outside Diameter: 20.500 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.181 inches Maximum Pressure Rating: 1500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material: Steel outer ring Material Specification: Milli-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips 12 size and 1500 series Shelf Life: N/A Unit Of Measure:	Aperture Diameter:
0.922 inches Gage Ring Outside Diameter: 20.500 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.131 inches Maximum Pressure Rating: 1500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips12 size and 1500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig: A032a0 Mil-std (military Standard):	12.875 inches
Gage Ring Outside Diameter: 20.500 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.131 inches Maximum Pressure Rating: 1500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167	Bearing Surface Width:
20.500 inches  Cross-sectional Thickness: Between 0.170 inches and 0.180 inches  Gage Ring Thickness: Between 0.117 inches and 0.131 inches  Maximum Pressure Rating: 1500.0 pounds per square inch  Environmental Attribute Code: Asbestos alternative products  Material: Steel outer ring  Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler on the standard 2nd material response spiral wound filler  Style Designator: Circular  Specification Or Standard: 2 type and a class and ips12 size and 1500 series  Shelf Life: N/a  Unit Of Measure:  ———————————————————————————————————	0.922 inches
Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 1500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips12 size and 1500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A03230 Mil-std (military Standard):	Gage Ring Outside Diameter:
Between 0.170 inches and 0.180 inches  Gage Ring Thickness: Between 0.117 inches and 0.131 inches  Maximum Pressure Rating: 1500.0 pounds per square inch  Environmental Attribute Code: Asbestos alternative products  Material: Steel outer ring  Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and ast	20.500 inches
Gage Ring Thickness: Between 0.117 inches and 0.131 inches  Maximum Pressure Rating: 1500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products  Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler wound filler  Style Designator: Circular Specification Or Standard: 2 type and a class and ips12 size and 1500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A03230 Mil-std (military Standard):	Cross-sectional Thickness:
Between 0.117 inches and 0.131 inches  Maximum Pressure Rating: 1500.0 pounds per square inch  Environmental Attribute Code: Asbestos alternative products  Material: Steel outer ring  Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler  Style Designator: Circular  Style Dasignator: Circular  Specification Or Standard: 2 type and a class and ips12 size and 1500 series  Shelf Life: N/a  Unit Of Measure:   Demilitarization: No  Fiig: A032a0  Mil-std (military Standard):	Between 0.170 inches and 0.180 inches
Maximum Pressure Rating: 1500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips12 size and 1500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A032a0 Mil-std (military Standard):	Gage Ring Thickness:
1500.0 pounds per square inch  Environmental Attribute Code: Asbestos alternative products  Material: Steel outer ring  Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral woun	Between 0.117 inches and 0.131 inches
Environmental Attribute Code: Asbestos alternative products  Material: Steel outer ring Material Specification: Mili-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler  Style Designator: Circular Specification Or Standard: 2 type and a class and ips12 size and 1500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mili-std (military Standard):	Maximum Pressure Rating:
Asbestos alternative products  Material: Steel outer ring  Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler  Style Designator: Circular Specification Or Standard: 2 type and a class and ips12 size and 1500 series  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	1500.0 pounds per square inch
Material: Steel outer ring  Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler style Designator: Circular Specification Or Standard: 2 type and a class and ips12 size and 1500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg: A032a0 Mil-std (military Standard):	Environmental Attribute Code:
Material Specification:  Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler style Designator:  Circular  Specification Or Standard: 2 type and a class and ips12 size and 1500 series  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:  A032a0  Mil-std (military Standard):	Asbestos alternative products
Material Specification:  Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler  Style Designator:  Circular  Specification Or Standard: 2 type and a class and ips12 size and 1500 series  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:  A032a0  Mil-std (military Standard):	Material:
Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler  Style Designator: Circular Specification Or Standard: 2 type and a class and ips12 size and 1500 series  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Steel outer ring
spiral wound filler  Style Designator: Circular  Specification Or Standard: 2 type and a class and ips12 size and 1500 series  Shelf Life: N/a Unit Of Measure: Demilitarization: No  Fiig: A032a0  Mil-std (military Standard):	Material Specification:
Style Designator: Circular  Specification Or Standard: 2 type and a class and ips12 size and 1500 series  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response
Circular  Specification Or Standard: 2 type and a class and ips12 size and 1500 series  Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A032a0 Mil-std (military Standard):	spiral wound filler
Specification Or Standard: 2 type and a class and ips12 size and 1500 series  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Style Designator:
2 type and a class and ips12 size and 1500 series  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Circular
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Specification Or Standard:
N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	2 type and a class and ips12 size and 1500 series
Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Shelf Life:
Demilitarization:  No Fiig: A032a0 Mil-std (military Standard):	N/a
Demilitarization:  No Fiig: A032a0 Mil-std (military Standard):	Unit Of Measure:
No Fiig: A032a0 Mil-std (military Standard):	
Fiig: A032a0 Mil-std (military Standard):	Demilitarization:
A032a0 Mil-std (military Standard):	No
Mil-std (military Standard):	Fiig:
	A032a0
Mil-p-24503 spec.	Mil-std (military Standard):
	Mil-p-24503 spec.