NSN 5330-01-338-7906

Spiral Wound Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-01-338-7906

Tempurature Rating: 900.0 degrees fahrenheit Outside Diameter: 10.344 inches Aperture Diameter: 8.875 inches Bearing Surface Width: 0.735 inches Gage Ring Outside Diameter: 13.875 inches
900.0 degrees fahrenheit Outside Diameter: 10.344 inches Aperture Diameter: 8.875 inches Bearing Surface Width: 0.735 inches Gage Ring Outside Diameter: 13.875 inches
Outside Diameter: 10.344 inches Aperture Diameter: 8.875 inches Bearing Surface Width: 0.735 inches Gage Ring Outside Diameter: 13.875 inches
10.344 inches Aperture Diameter: 8.875 inches Bearing Surface Width: 0.735 inches Gage Ring Outside Diameter: 13.875 inches
Aperture Diameter: 8.875 inches Bearing Surface Width: 0.735 inches Gage Ring Outside Diameter: 13.875 inches
8.875 inches Bearing Surface Width: 0.735 inches Gage Ring Outside Diameter: 13.875 inches
Bearing Surface Width: 0.735 inches Gage Ring Outside Diameter: 13.875 inches
0.735 inches Gage Ring Outside Diameter: 13.875 inches
Gage Ring Outside Diameter: 13.875 inches
13.875 inches
13.875 inches Cross-sectional Thickness:
Cross-sectional Thickness:
Between 0.170 inches and 0.180 inches
Gage Ring Thickness:
Between 0.117 inches and 0.131 inches
Maximum Pressure Rating:
1500.0 pounds per square inch
Environmental Attribute Code:
Asbestos alternative products
Material:
Steel outer ring
Material Specification:
Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response
spiral wound filler
Style Designator:
Circular
Specification Or Standard:
2 type and b class and ips8 size and 1500 series
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A032a0
Mil-std (military Standard):
Mil-p-24503 spec.