NSN 5330-01-338-7923

Spiral Wound Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-01-338-7923

Metal winding w/ soft filler and outer ring Tempurature Rating: 10:05:0.0 degrees fahrenheit Outside Diameter: 6.969 inches Aperture Diameter: 6.969 inches Bearing Surface Wildth: 0.672 inches Bearing Surface Wildth: 0.672 inches Bearing Surface Wildth: 0.672 inches Gage Ring Outside Diameter: 11:000 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.170 inches and 0.131 inches Maximum Pressure Rating: 2500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mili-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standard 2nd material response spiral wound filler and astm a168 assn standa	
Tempurature Rating: 1050.0 degrees fahrenheit Outside Diameter: 5.825 inches Aperture Diameter: 5.825 inches Bearing Surface Width: 0.672 inches Gage Ring Outside Diameter: 11.000 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.131 inches Maximum Pressure Rating: 2500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Siteel outer ring Material Specification: Mili-p-24503, type 1, ol 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and a standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips5 size and 2500 series Shelf Life: No Unit Of Measure: — Demilitarization: No Filig: 403230 Mili-std (military Standard):	Cross Sectional Shape:
1050.0 degrees fahrenheit Outside Diameter: 6.096 inches Apperture Diameter: 5.625 inches Bearing Surface Width: 0.672 inches Bearing Surface Width: 0.672 inches Gage Ring Outside Diameter: 11.000 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.131 inches Maximum Pressure Rating: 2500.0 pounds per square inch Environmental Attribute Code: Aabeatos alternative products Material: Steel outer ring Material Specification: Whit-p-24503, type 1, ol 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and active and active act	Metal winding w/ soft filler and outer ring
Outside Diameter: 5.959 inches Aperture Diameter: 5.525 inches Bearing Surface Width: 0.672 inches Bearing Surface Width: 0.672 inches Gage Ring Outside Diameter: 11.000 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.131 inches Maximum Pressure Rating: 2500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response and a class and a cla	Tempurature Rating:
Aperture Diameter: 5.625 inches Bearing Surface Width: 0.672 inches Gage Ring Outside Diameter: 11.000 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.170 inches and 0.181 inches Maximum Pressure Rating: 2500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Siteel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167	1050.0 degrees fahrenheit
Aperture Diameter: 5.625 inches Bearing Surface Width: 0.672 inches Gage Ring Outside Diameter: 11.000 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.181 inches Maximum Pressure Rating: 2500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material: Steel outer ring Material Specification: Mit-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips5 size and 2500 series Shelf Life: No Unit Of Measure: — Demilitarization: No Filig: A032a0 Mili-std (military Standard):	Outside Diameter:
Bearing Surface Width: 0.672 inches Gage Ring Outside Diameter: 111.000 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.181 inches Maximum Pressure Rating: 250.00 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips5 size and 2500 series Shelf Life: No Unit Of Measure: — Demilitarization: No Fifig: A032a0 Mil-std (military Standard):	6.969 inches
Bearing Surface Width: 0.672 inches Gage Ring Outside Diameter: 11.000 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.181 inches Maximum Pressure Rating: 2500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material: Steel outer ring Material Specification: Mili-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips5 size and 2500 series Shelf Life: N/A Unit Of Measure: — Demilitarization: No Fifig: A032a0 Mili-std (military Standard):	Aperture Diameter:
0.672 inches Gage Ring Outside Diameter: 11.000 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.131 inches Maximum Pressure Rating: 2500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips5 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig: A032a0 Mil-std (military Standard):	5.625 inches
Gage Ring Outside Diameter: 11.000 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.131 inches Maximum Pressure Rating: 250.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips5 size and 2500 series Shelf Life: N/a Unit Of Measure: ———————————————————————————————————	Bearing Surface Width:
11.000 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 2500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips5 size and 2500 series Shelf Life: N/a Unit Of Measure: ————————————————————————————————————	0.672 inches
Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 2500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips5 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A03230 Mil-std (military Standard):	Gage Ring Outside Diameter:
Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 2500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and ast	11.000 inches
Gage Ring Thickness: Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 2500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips5 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A03230 Mil-std (military Standard):	Cross-sectional Thickness:
Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 2500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Style Dasignator: Circular Specification Or Standard: 2 type and a class and ips5 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Between 0.170 inches and 0.180 inches
Maximum Pressure Rating: 2500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips5 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A032a0 Mil-std (military Standard):	Gage Ring Thickness:
2500.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips5 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A032a0 Mili-std (military Standard):	Between 0.117 inches and 0.131 inches
Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mili-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips5 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mili-std (military Standard):	Maximum Pressure Rating:
Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips5 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	2500.0 pounds per square inch
Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler style Designator: Circular Specification Or Standard: 2 type and a class and ips5 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg: A032a0 Mil-std (military Standard):	Environmental Attribute Code:
Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler style Designator: Circular Specification Or Standard: 2 type and a class and ips5 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A032a0 Mil-std (military Standard):	Asbestos alternative products
Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips5 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Material:
Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips5 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Steel outer ring
spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and a class and ips5 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Material Specification:
Style Designator: Circular Specification Or Standard: 2 type and a class and ips5 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm a167 assn standard 2nd material response
Circular Specification Or Standard: 2 type and a class and ips5 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A032a0 Mil-std (military Standard):	spiral wound filler
Specification Or Standard: 2 type and a class and ips5 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Style Designator:
2 type and a class and ips5 size and 2500 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Circular
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Specification Or Standard:
N/a Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	2 type and a class and ips5 size and 2500 series
Unit Of Measure: Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Shelf Life:
Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	N/a
Demilitarization: No Fiig: A032a0 Mil-std (military Standard):	Unit Of Measure:
No Fiig: A032a0 Mil-std (military Standard):	
Fiig: A032a0 Mil-std (military Standard):	Demilitarization:
A032a0 Mil-std (military Standard):	No
Mil-std (military Standard):	Fiig:
	A032a0
Mil-p-24503 spec.	Mil-std (military Standard):
	Mil-p-24503 spec.