## NSN 5330-01-338-7928

Spiral Wound Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-01-338-7928

| Cross Sectional Shape:   |
|--|
| Metal winding w/ soft filler and outer ring  |
| Tempurature Rating:  |
| 900.0 degrees fahrenheit   |
| Outside Diameter:  |
| 6.969 inches   |
| Aperture Diameter:   |
| 6.125 inches   |
| Bearing Surface Width:   |
| 0.422 inches   |
| Gage Ring Outside Diameter:  |
| 7.750 inches   |
| Cross-sectional Thickness:   |
| Between 0.170 inches and 0.180 inches  |
| Gage Ring Thickness:   |
| Between 0.117 inches and 0.131 inches  |
| Maximum Pressure Rating:   |
| 150.0 pounds per square inch   |
| Environmental Attribute Code:  |
| Asbestos alternative products  |
| Material:  |
| Steel outer ring   |
| Material Specification:  |
| Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b168 assn standard 2nd material response |
| spiral wound filler  |
| Style Designator:  |
| Circular   |
| Specification Or Standard:   |
| 2 type and b class and ips5 size and 150 series  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| -  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A032a0   |
| Mil-std (military Standard):   |
| Mil-p-24503 spec.  |
|  |