NSN 5330-01-341-9340

Gasket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5330-01-341-9340

| Cross Sectional Shape: |
|---|
| Solid single or composition |
| Hole Diameter: |
| Between 0.135 inches and 0.197 inches |
| Overall Length: |
| 4.500 inches |
| Overall Width: |
| 2.880 inches |
| Outside Corner Radius: |
| 0.060 inches |
| Center To Center Distance Between Bolt Holes Along Width: |
| 2.440 inches |
| Center To Center Distance Between Bolt Holes Along Length: |
| 2.030 inches |
| Outside Edge To Bolt Hole Center Distance Along Width: |
| 0.220 inches |
| Outside Edge To Bolt Hole Center Distance Along Length: |
| 0.220 inches |
| Cross-sectional Thickness: |
| 0.125 inches |
| Bolt Hole Quantity: |
| 6 |
| Criticality Code Justification: |
| Zzzy |
| Material: |
| Rubber silicone class q |
| Material Specification: |
| Zz-r-765, class 2a federal specification single material response |
| Special Test Features: |
| Special quality control testing |
| Style Designator: |
| Non-circular Section 1. The section |
| Test Data Document: |
| 81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Reference Number Differentiating Characteristics: |
| As differentiated by material which must conform to ships parts control center special quality control provisions |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |

No

NSN 5330-01-341-9340

Gasket - Page 2 of 2



Fiig:

A032a0