NSN 5330-01-347-5085

Gasket - Page 1 of 2

Fiig: A032a0



View Online at https://aerobasegroup.com/nsn/5330-01-347-5085

| Cross Sectional Shape: |
|--|
| Solid single or composition |
| Hole Diameter: |
| 0.310 inches |
| Overall Length: |
| 23.560 inches |
| Overall Width: |
| 0.620 inches |
| Center To Center Distance Between Bolt Holes Along Length: |
| 4.420 inches |
| Outside Edge To Bolt Hole Center Distance Along Length: |
| 0.720 inches |
| Bolt Hole Centerline To Nearest Edge Distance: |
| 0.310 inches |
| Cross-sectional Thickness: |
| 0.120 inches |
| Bolt Hole Quantity: |
| 6 |
| Criticality Code Justification: |
| Zzzy |
| Color: |
| Orange |
| Material: |
| Rubber silicone class q |
| Material Specification: |
| Mil-r-46089 grm military specification single material response |
| Special Test Features: |
| Special quality control testing |
| Style Designator: |
| Non-circular |
| Test Data Document: |
| 81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Reference Number Differentiating Characteristics: |
| As differentiated by material which must conform to ships parts control center special quality control provisions |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

NSN 5330-01-347-5085

Gasket - Page 2 of 2



Mil-std (military Standard):

Mil-r-46089 spec.