NSN 5330-01-347-8148

Gasket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5330-01-347-8148

| Cross Sectional Shape: |
|---------------------------------------------------------------------------------------------------------------------------------|
| Solid single or composition |
| Hole Diameter: |
| 0.281 inches |
| Overall Length: |
| 2.438 inches |
| Overall Width: |
| 1.562 inches |
| Inside Corner Radius: |
| 0.125 inches |
| Outside Corner Radius: |
| 0.281 inches |
| Aperture Width: |
| 1.000 inches |
| Aperture Length: |
| 1.312 inches |
| Center To Center Distance Between Bolt Holes Along Width: |
| 0.500 inches |
| Center To Center Distance Between Bolt Holes Along Length: |
| 1.875 inches |
| Outside Edge To Bolt Hole Center Distance Along Width: |
| 0.281 inches |
| Outside Edge To Bolt Hole Center Distance Along Length: |
| 0.281 inches |
| Cross-sectional Thickness: |
| 0.031 inches |
| Bolt Hole Quantity: |
| 4 |
| Criticality Code Justification: |
| Matt |
| Environmental Attribute Code: |
| Asbestos alternative products |
| Material: |
| Plastic or rubber or leather or fiber |
| Material Specification: |
| Mil-g-12803, type 7 military specification all material responses or astm f104 712400e45-6 assn standard all material responses |
| Reference Number Differentiating Characteristics: |
| As differentiated by non-asbestos material |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 5330-01-347-8148

Gasket - Page 2 of 2



| em | | | |
|----|--|--|--|
| | | | |
| | | | |

No

Fiig:

A032a0

Mil-std (military Standard):

Mil-g-12803 spec.