

View Online at <https://aerobasegroup.com/nsn/5330-01-381-0911>

**Cross Sectional Shape:**

Solid single or composition

**Hole Diameter:**

Between 0.115 inches and 0.125 inches

**Overall Length:**

Between 5.490 inches and 5.510 inches

**Overall Width:**

Between 5.210 inches and 5.230 inches

**Center To Center Distance Between Bolt Holes Along Width:**

Between 1.240 inches and 1.260 inches

**Center To Center Distance Between Bolt Holes Along Length:**

Between 1.310 inches and 1.330 inches

**Outside Edge To Bolt Hole Center Distance Along Width:**

Between 0.109 inches and 0.111 inches

**Outside Edge To Bolt Hole Center Distance Along Length:**

Between 0.108 inches and 0.110 inches

**Cross-sectional Thickness:**

Between 0.010 inches and 0.020 inches

**Bolt Hole Quantity:**

16

**End Application:**

Pacer dawn

**Hardness Rating:**

35.0 shore durometer a and 45.0 shore durometer a

**Outside Edge To Inside Edge Smallest Distance Along Width:**

Between 0.240 inches and 0.260 inches

**Outside Edge To Inside Edge Smallest Distance Along Length:**

Between 0.240 inches and 0.260 inches

**Material:**

Rubber butadiene-acrylonitrile class nbr

**Material Specification:**

Mil-r-6855/1 military specification single material response

**Style Designator:**

Non-circular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A032a0

**Mil-std (military Standard):**

Mil-r-6855 spec.