NSN 5330-01-425-2637

Gasket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5330-01-425-2637

Cross	Se	ction	nal	Sha	ne:
UI U33	OC.	CLICI	ıaı	ulia	vc.

Solid single or composition

Hole Diameter:

Between 0.110 inches and 0.130 inches

Overall Length:

Between 1.508 inches and 1.524 inches

Overall Width:

Between 1.508 inches and 1.524 inches

Aperture Diameter:

Between 1.312 inches and 1.338 inches

Outside Corner Radius:

Between 0.162 inches and 0.182 inches

Center To Center Distance Between Bolt Holes Along Width:

Between 1.130 inches and 1.150 inches

Center To Center Distance Between Bolt Holes Along Length:

Between 1.005 inches and 1.025 inches

Outside Edge To Bolt Hole Center Distance Along Width:

0.198 inches

Outside Edge To Bolt Hole Center Distance Along Length:

0.198 inches

Cross-sectional Thickness:

Between 0.026 inches and 0.036 inches

Bolt Hole Quantity:

Elongation Percentage:

125

Hardness Rating:

50.0 shore durometer a

Color:

Blue

Material:

Rubber fluorosilicone class fq

Material Specification:

Mil-r-25988 military specification single material response

Style Designator:

Non-circular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5330-01-425-2637

Gasket - Page 2 of 2



Fiig:

A032a0

Mil-std (military Standard):

Mil-r-25988 spec.