NSN 5330-01-446-7974

Spiral Wound Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5330-01-446-7974

spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and c class and ips3 size and 900 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0	
Tempurature Rating: 700.0 degrees fahrenheit Outside Diameter: 4.719 inches Aperture Diameter: 3.750 inches Bearing Surface Width: 0.485 inches Gage Ring Outside Diameter: 6.825 inches Gage Ring Outside Diameter: 6.825 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.170 inches and 0.131 inches Maximum Pressure Rating: 900.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and c class and ips3 size and 900 series Shelf Life: No Unit Of Measure: Demilitarization: No Filig: A03280	Cross Sectional Shape:
700.0 degrees fahrenheit Outside Diameter: 4.719 inches Aperture Diameter: 3.750 inches Bearing Surface Width: 0.485 inches Bearing Surface Width: 0.485 inches Gage Ring Outside Diameter: 6.625 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.170 inches and 0.131 inches Maximum Pressure Rating: 900.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Specification Or Standard: 2 type and c class and ips3 size and 900 series Shelf Life: Na Unit Of Measure: — Demilitarization: No Fitg: H03200	Metal winding w/ soft filler and outer ring
Outside Diameter: 4.719 inches Aperture Diameter: 3.750 inches Bearing Surface Width: 0.485 inches Gage Ring Outside Diameter: 6.825 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.181 inches Maximum Pressure Rating: 900.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Milip-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and c class and ips3 size and 900 series Shelf Life: N/a Unit Of Measure: — Demilitarization: No Filig: A032a0	Tempurature Rating:
4.719 inches Aperture Diameter: 3.750 inches Bearing Surface Width: 0.485 inches Gage Ring Outside Diameter: 6.625 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.181 inches Maximum Pressure Rating: 900.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mili-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and c class and ips3 size and 900 series Sheff Life: Na Unit Of Measure: — Demilitarization: No Filig: A032a0	700.0 degrees fahrenheit
Aperture Diameter: 3.750 inches Bearing Surface Width: 0.485 inches Gage Ring Outside Diameter: 6.625 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.170 inches and 0.131 inches Maximum Pressure Rating: 900.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mili-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler and actin b127 assn standard 2nd material response spiral wound filler and actin b127 assn standard 2nd material response spiral wound filler and actin b127 assn standard 2nd material response spiral wound filler and actin b127 assn standard 2nd material response spiral wound filler and actin b127 assn standard 2nd material response spiral wound filler and actin b127 assn standard 2nd material response spiral wound filler and actin b127 assn standard 2nd material response spiral wound filler and actin b127 assn standard 2nd material response spiral wound filler and actin b127 assn standard 2nd material response spiral wound filler and actin b127 assn standard 2nd material response spiral wound filler and actin b127 assn standard 2nd material response spiral wound filler and actin b127 assn standard 2nd material response spiral wound filler and actin b127 assn standard 2nd material response spiral wound filler and actin b127 assn standard 2nd material response spiral wound filler and actin b127 assn standard 2nd material response spiral wound filler and actin b127 assn standard 2nd material response spiral wound filler and actin b127 assn standard 2nd material response spiral wound filler and actin b127 assn standard 2nd material response spiral wound filler and actin b127 assn standard 2nd material response spiral wound filler and actin b127 assn standard 2nd material response spiral wound filler and actin b127 assn standard 2nd material response spiral wound fi	Outside Diameter:
Bearing Surface Width: 0.485 inches Gage Ring Outside Diameter: 6.825 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.131 inches Maximum Pressure Rating: 90.00 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and c class and ips3 size and 900 series Sheft Life: N/a Unit Of Measure:	4.719 inches
Bearing Surface Width: 0.485 inches Gage Ring Outside Diameter: 6.625 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.181 inches Maximum Pressure Rating: 90.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and c class and ips3 size and 900 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0	Aperture Diameter:
0.485 inches Gage Ring Outside Diameter: 6.625 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.181 inches Maximum Pressure Rating: 900.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mili-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Steel outer filler Specification Or Standard: 2 type and c class and ips3 size and 900 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A032a0	3.750 inches
Gage Ring Outside Diameter: 6.625 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.171 inches and 0.131 inches Maximum Pressure Rating: 900.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503. type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and c class and ips3 size and 900 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A032a0	Bearing Surface Width:
6.625 inches Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 900.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 millitary specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and c class and ips3 size and 900 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0	0.485 inches
Cross-sectional Thickness: Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 90.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and c class and ips3 size and 900 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A032a0	Gage Ring Outside Diameter:
Between 0.170 inches and 0.180 inches Gage Ring Thickness: Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 900.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Style Designator: Circular Style Designator: Circular Style Inches and 0.180 inps3 size and 900 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A032a0	6.625 inches
Gage Ring Thickness: Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 900.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Style Designator: Circular Style Designator: Circular Specification Or Standard: 2 type and c class and ips3 size and 900 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A032a0	Cross-sectional Thickness:
Between 0.117 inches and 0.131 inches Maximum Pressure Rating: 900.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and c class and ips3 size and 900 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A032a0	Between 0.170 inches and 0.180 inches
Maximum Pressure Rating: 900.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and c class and ips3 size and 900 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0	Gage Ring Thickness:
900.0 pounds per square inch Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and c class and ips3 size and 900 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0	Between 0.117 inches and 0.131 inches
Environmental Attribute Code: Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and c class and ips3 size and 900 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0	Maximum Pressure Rating:
Asbestos alternative products Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and c class and ips3 size and 900 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0	900.0 pounds per square inch
Material: Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and c class and ips3 size and 900 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A032a0	Environmental Attribute Code:
Steel outer ring Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and c class and ips3 size and 900 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0	Asbestos alternative products
Material Specification: Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and c class and ips3 size and 900 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0	Material:
Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and c class and ips3 size and 900 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0	Steel outer ring
spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler Style Designator: Circular Specification Or Standard: 2 type and c class and ips3 size and 900 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0	Material Specification:
Style Designator: Circular Specification Or Standard: 2 type and c class and ips3 size and 900 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0	Mil-p-24503, type 1, cl 2 military specification 1st material response spiral wound filler and astm b127 assn standard 2nd material response
Circular Specification Or Standard: 2 type and c class and ips3 size and 900 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0	spiral wound filler or qq-n-281, cl a federal specification 2nd material response spiral wound filler
Specification Or Standard: 2 type and c class and ips3 size and 900 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0	Style Designator:
2 type and c class and ips3 size and 900 series Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0	Circular
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A032a0	Specification Or Standard:
N/a Unit Of Measure: Demilitarization: No Fiig: A032a0	2 type and c class and ips3 size and 900 series
Unit Of Measure: Demilitarization: No Fiig: A032a0	Shelf Life:
Demilitarization: No Fiig: A032a0	N/a
No Fiig: A032a0	Unit Of Measure:
No Fiig: A032a0	
Fiig: A032a0	Demilitarization:
A032a0	No
	Fiig:
Mil. std (military Standard):	A032a0
min-stu (ininital y Statiualu).	Mil-std (military Standard):
Mil-p-24503 spec.	Mil-p-24503 spec.