

View Online at <https://aerobasegroup.com/nsn/5330-01-447-2183>

Cross Sectional Shape:

Solid single or composition

Hole Diameter:

Between 0.105 inches and 0.145 inches

Overall Length:

Between 6.460 inches and 6.540 inches

Overall Width:

Between 1.460 inches and 1.540 inches

Inside Corner Radius:

0.125 inches

Outside Corner Radius:

0.125 inches

Aperture Width:

Between 0.720 inches and 0.780 inches

Aperture Length:

Between 5.710 inches and 5.790 inches

Outside Edge To Bolt Hole Center Distance Along Width:

0.750 inches

Cross-sectional Thickness:

0.032 inches

Bolt Hole Quantity:

2

Hardness Rating:

45.0 shore durometer a and 55.0 shore durometer a

Criticality Code Justification:

Zzzy

Outside Edge To Inside Edge Smallest Distance Along Width:

0.375 inches

Outside Edge To Inside Edge Smallest Distance Along Length:

0.375 inches

Material:

Rubber silicone class q

Material Specification:

Astm d2000, fc, fe, ge assn standard single material response

Special Test Features:

Special quality control testing

Style Designator:

Non-circular

Test Data Document:

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Reference Number Differentiating Characteristics:

As differentiated by material which must conform to ships parts control center special quality control provisions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A032a0