

View Online at <https://aerobasegroup.com/nsn/5330-01-506-9620>

**Tempurature Rating:**

450.0 degrees fahrenheit

**Cross-sectional Height:**

0.250 inches

**Center Hole Diameter:**

0.875 inches

**Peripheral Diameter:**

1.375 inches

**Lubrication Method:**

Impregnated

**End Application:**

USED-ON-6"T-.T.F

**Product Name:**

Packing ring

**Hazardous Substances:**

Oil and plastic

**Lubrication Material:**

Oil

**Material:**

Plastic polyurethane

**Supplementary Features:**

Intended for dynamic service and shipboard fluids except superheated steam or other service resulting in packing temperatures of over 450 degrees fahrenheit oxygen, molten alkaline metals, or fluorochemicals; pressures should not exceed 150 pounds per square inch at the packing, and rod or shaft speed should not exceed 1, 5000 feet per minute

**Test Data Document:**

81349-mil-p-24396 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-p-24396 government specification

**Specification Or Standard:**

A type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A032a0