

View Online at <https://aerobasegroup.com/nsn/5330-01-506-9620>

Tempurature Rating:

450.0 degrees fahrenheit

Cross-sectional Height:

0.250 inches

Center Hole Diameter:

0.875 inches

Peripheral Diameter:

1.375 inches

Lubrication Method:

Impregnated

End Application:

USED-ON-6"T-.T.F

Product Name:

Packing ring

Hazardous Substances:

Oil and plastic

Lubrication Material:

Oil

Material:

Plastic polyurethane

Supplementary Features:

Intended for dynamic service and shipboard fluids except superheated steam or other service resulting in packing temperatures of over 450 degrees fahrenheit oxygen, molten alkaline metals, or fluorochemicals; pressures should not exceed 150 pounds per square inch at the packing, and rod or shaft speed should not exceed 1, 5000 feet per minute

Test Data Document:

81349-mil-p-24396 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-p-24396 government specification

Specification Or Standard:

A type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A032a0