
NSN 5330-01-509-1340

Gasket - Page 1 of 2



Cross Sectional Shape:

Solid single or composition

Hole Diameter:

3.7 millimeters

Overall Length:

Between 287.9 millimeters and 294.4 millimeters

Overall Width:

Between 151.4 millimeters and 154.9 millimeters

Outside Corner Radius:

4.0 millimeters

Aperture Width:

143.4 millimeters

Aperture Length:

282.9 millimeters

Inside Corner Bevel Length Along Width:

8.5 millimeters

Inside Corner Bevel Length Along Length:

8.5 millimeters

Center To Center Distance Between Bolt Holes Along Width:

Between 71.6 millimeters and 73.6 millimeters

Center To Center Distance Between Bolt Holes Along Length:

Between 69.9 millimeters and 71.9 millimeters

Outside Edge To Bolt Hole Center Distance Along Width:

4.1 millimeters

Outside Edge To Bolt Hole Center Distance Along Length:

4.1 millimeters

Cross-sectional Thickness:

Between 1.27 millimeters and 1.87 millimeters

Bolt Hole Quantity:

12

Hardness Rating:

40.0 shore durometer a and 50.0 shore durometer a

Product Name:

Gasket-sealing, heatsink

Material:

Rubber silicone class q

Material Specification:

Zz-r-765 cl 2a federal specification single material response

Style Designator:

Non-circular

Shelf Life:

N/a



NSN 5330-01-509-1340

Gasket - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A032a0

