

View Online at <https://aerobasegroup.com/nsn/5330-01-595-7366>

**End Application:**

Operator housing assembly. Lockout ballscrew assembly

**Construction:**

One-piece

**Criticality Code Justification:**

Zzzy

**Special Features:**

Items referencing "dss-fc" in the remarks column of the parts list, material list, or joint list (as applicable) are those items within the dss-soc boundry which are full compliance (fc) as defined in the nssn dss certification program plan. These items shall meet the requirements specified on the drawing/diagram and require unique dss-soc re-entry control.

**Material:**

Steel

**Supplementary Features:**

(1) apply anerobic compound. Mil-s-46163a1. Grade n. (eb pn e8211064199) to the bore in the bearing adapter, 'pn 21. For the grease seal on 22. Drive the grese seal into the bearing adapter bore with a suitable seal driver. (2) where this note is referenced, at assembly apply a coat of permatex seal (ep pn 54-80-0600a) to surfaces of pn 21 that comes in contact with pn 20.

**Reference Number Differentiating Characteristics:**

Material controlled iaw ss800-ag-man-010/p-9290 system certification procedures and criteria manual for deep submergence systems. Critical item for safety and survival of deep submergence research and rescue vehicles as differentiated by special test features.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A032a0