

View Online at <https://aerobasegroup.com/nsn/5330-01-595-7366>

End Application:

Operator housing assembly. Lockout ballscrew assembly

Construction:

One-piece

Criticality Code Justification:

Zzzy

Special Features:

Items referencing "dss-fc" in the remarks column of the parts list, material list, or joint list (as applicable) are those items within the dss-soc boundry which are full compliance (fc) as defined in the nssn dss certification program plan. These items shall meet the requirements specified on the drawing/diagram and require unique dss-soc re-entry control.

Material:

Steel

Supplementary Features:

(1) apply anerobic compound. Mil-s-46163a1. Grade n. (eb pn e8211064199) to the bore in the bearing adapter, 'pn 21. For the grease seal on 22. Drive the grese seal into the bearing adapter bore with a suitable seal driver. (2) where this note is referenced, at assembly apply a coat of permatex seal (ep pn 54-80-0600a) to surfaces of pn 21 that comes in contact with pn 20.

Reference Number Differentiating Characteristics:

Material controlled iaw ss800-ag-man-010/p-9290 system certification procedures and criteria manual for deep submergence systems. Critical item for safety and survival of deep submergence research and rescue vehicles as differentiated by special test features.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A032a0