

View Online at <https://aerobasegroup.com/nsn/5330-01-657-2743>

**Cross Sectional Shape:**

Solid single or composition

**Hole Diameter:**

0.151 inches and 0.161 inches all holes

**Overall Length:**

Between 6.990 inches and 7.010 inches

**Overall Width:**

Between 4.990 inches and 5.010 inches

**Aperture Width:**

Between 4.190 inches and 4.210 inches

**Aperture Length:**

Between 6.190 inches and 6.210 inches

**Outside Corner Bevel Length Along Width:**

Between 0.190 inches and 0.210 inches

**Outside Corner Bevel Length Along Length:**

Between 0.190 inches and 0.210 inches

**Center To Center Distance Between Bolt Holes Along Width:**

2.490 inches and 2.510 inches all holes

**Center To Center Distance Between Bolt Holes Along Length:**

2.240 inches and 2.260 inches all holes

**Outside Edge To Bolt Hole Center Distance Along Width:**

Between 0.190 inches and 0.210 inches

**Outside Edge To Bolt Hole Center Distance Along Length:**

Between 1.240 inches and 1.260 inches

**Cross-sectional Thickness:**

Between 0.057 inches and 0.067 inches

**Bolt Hole Quantity:**

10

**End Application:**

Meter

**Outside Edge To Inside Edge Smallest Distance Along Width:**

Between 0.390 inches and 0.410 inches

**Outside Edge To Inside Edge Smallest Distance Along Length:**

Between 0.390 inches and 0.410 inches

**Product Name:**

Gasket, front panel, aps

**Material:**

Rubber neoprene

**Material Specification:**

Mil-r-6855, class 2, type b, grade 60, adhesive backed military specification single material response

**Style Designator:**

Non-circular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A032a0

**Mil-std (military Standard):**

Mil-r-6855 spec.