## NSN 5335-01-299-7705

Wire Fabric - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5335-01-299-7705

Fabrication Method:
Interwoven
Length:
Between 8.470 inches and 8.530 inches
Edge Type:
Plain edge
Surface Treatment Application Stage:
After fabrication
Weave Type:
Plain square
Wire Crimp Type:
Any acceptable
Mesh Length To Warp Direction:
Longitudinal
Filament Location:
Special Features:
Special Features: 6 holes 0.180 in. Min, 0.212 in. Maximum dia
6 holes 0.180 in. Min, 0.212 in. Maximum dia
6 holes 0.180 in. Min, 0.212 in. Maximum dia  Surface Treatment:
6 holes 0.180 in. Min, 0.212 in. Maximum dia  Surface Treatment:  Passivate
6 holes 0.180 in. Min, 0.212 in. Maximum dia  Surface Treatment:  Passivate  Shape:
6 holes 0.180 in. Min, 0.212 in. Maximum dia  Surface Treatment:  Passivate  Shape:  Rectangular
6 holes 0.180 in. Min, 0.212 in. Maximum dia  Surface Treatment:  Passivate  Shape:  Rectangular  Surface Treatment:
6 holes 0.180 in. Min, 0.212 in. Maximum dia  Surface Treatment:  Passivate  Shape:  Rectangular  Surface Treatment:  Passivated
6 holes 0.180 in. Min, 0.212 in. Maximum dia  Surface Treatment:  Passivate  Shape:  Rectangular  Surface Treatment:  Passivated  Shelf Life:
6 holes 0.180 in. Min, 0.212 in. Maximum dia  Surface Treatment:  Passivate  Shape:  Rectangular  Surface Treatment:  Passivated  Shelf Life:  N/a
6 holes 0.180 in. Min, 0.212 in. Maximum dia  Surface Treatment:  Passivate  Shape:  Rectangular  Surface Treatment:  Passivated  Shelf Life:  N/a
6 holes 0.180 in. Min, 0.212 in. Maximum dia  Surface Treatment:  Passivate  Shape:  Rectangular  Surface Treatment:  Passivated  Shelf Life:  N/a  Unit Of Measure:
6 holes 0.180 in. Min, 0.212 in. Maximum dia  Surface Treatment:  Passivate  Shape:  Rectangular  Surface Treatment:  Passivated  Shelf Life:  N/a  Unit Of Measure:   Demilitarization: