

View Online at <https://aerobasegroup.com/nsn/5340-00-001-9668>

First Leg Length:

1.438 inches

Second Leg Length:

1.921 inches

Second Leg Width:

1.500 inches

First Leg Hole Diameter:

Between 0.5615 inches and 0.5625 inches

Second Leg Hole Diameter:

Between 0.127 inches and 0.133 inches

Second Leg Distance Between Hole Centers Along Width:

0.860 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

0.640 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

0.220 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.540 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.187 inches

Second Leg Distance Between First And Second Hole Centers Along Length:

0.640 inches

Second Leg Distance Between Second And Third Hole Centers Along Length:

0.421 inches

First Leg Thickness:

0.218 inches

Second Leg Thickness:

0.200 inches

First Leg Width:

1.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.469 inches

First Leg Distance From Edge To Hole Center Along Length:

0.469 inches

First Leg End Radius:

0.469 inches

Second Leg End Radius:

0.560 inches

First Leg Style:

End radius and tapered

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

100.0 degrees

Special Features:

Self-aligning bearing press fit and stake into one leg

Material:

Aluminum alloy

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.