

View Online at <https://aerobasegroup.com/nsn/5340-00-003-8368>

Mounting Hole Type:

Countersunk

First Leg Length:

0.765 inches

Second Leg Length:

0.875 inches

Second Leg Width:

Between 0.600 inches and 0.660 inches

First Leg Hole Diameter:

Between 0.124 inches and 0.129 inches

Second Leg Hole Diameter:

0.125 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.125 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.125 inches

First Leg Thickness:

0.265 inches

Second Leg Thickness:

Between 0.250 inches and 0.270 inches

First Leg Width:

Between 0.055 inches and 0.085 inches

First Leg Distance Between Hole Centers Along Length:

0.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.125 inches

First Leg Distance From Edge To Hole Center Along Length:

0.150 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Extended flat

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

135.0 degrees

Special Features:

All holes are drilled through first and second leg thickness

Heat Treatment:

T-4 solution heat treated

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-200/3 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.