## NSN 5340-00-006-8177

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-006-8177

First Leg Length:1.812 inchesSecond Leg Length:2.187 inchesSecond Leg Width:0.750 inchesFirst Leg Slot Length:0.500 inchesFirst Leg Slot Width:0.250 inchesSecond Leg Distance From Edge To Hole Center Along Width:0.375 inchesSecond Leg Distance From Edge To Hole Center Along Length:0.500 inchesSecond Leg Distance From Edge To Hole Center Along Length:0.500 inchesSecond Leg Slot Length:0.500 inchesSecond Leg Slot Length:0.500 inchesSecond Leg Slot Width:0.500 inchesSecond Leg Slot Width:0.500 inchesSecond Leg Slot Width:0.250 inchesSecond Leg Slot Width:0.250 inchesSecond Leg Slot Width:0.250 inchesSecond Leg Slot Width:0.240 inchesFirst Leg Thickness:0.040 inches
Second Leg Length: 2.187 inches Second Leg Width: 0.750 inches First Leg Slot Length: 0.500 inches First Leg Slot Width: 0.250 inches Second Leg Distance From Edge To Hole Center Along Width: 0.375 inches Second Leg Distance From Edge To Hole Center Along Length: 0.500 inches Second Leg Slot Length: 0.500 inches Second Leg Slot Width: 0.250 inches First Leg Thickness:
2.187 inches Second Leg Width: 0.750 inches First Leg Slot Length: 0.500 inches First Leg Slot Width: 0.250 inches Second Leg Distance From Edge To Hole Center Along Width: 0.375 inches Second Leg Distance From Edge To Hole Center Along Length: 0.500 inches Second Leg Slot Length: 0.500 inches Second Leg Slot Length: 0.250 inches First Leg Thickness:
Second Leg Width: 0.750 inches First Leg Slot Length: 0.500 inches First Leg Slot Width: 0.250 inches Second Leg Distance From Edge To Hole Center Along Width: 0.375 inches Second Leg Distance From Edge To Hole Center Along Length: 0.500 inches Second Leg Slot Length: 0.500 inches Second Leg Slot Width: 0.250 inches First Leg Thickness:
0.750 inches First Leg Slot Length: 0.500 inches First Leg Slot Width: 0.250 inches Second Leg Distance From Edge To Hole Center Along Width: 0.375 inches Second Leg Distance From Edge To Hole Center Along Length: 0.500 inches Second Leg Slot Length: 0.500 inches First Leg Slot Width: 0.250 inches
First Leg Slot Length:0.500 inchesFirst Leg Slot Width:0.250 inchesSecond Leg Distance From Edge To Hole Center Along Width:0.375 inchesSecond Leg Distance From Edge To Hole Center Along Length:0.500 inchesSecond Leg Slot Length:0.500 inchesSecond Leg Slot Width:0.250 inchesFirst Leg Thickness:
0.500 inches First Leg Slot Width: 0.250 inches Second Leg Distance From Edge To Hole Center Along Width: 0.375 inches Second Leg Distance From Edge To Hole Center Along Length: 0.500 inches Second Leg Slot Length: 0.500 inches Second Leg Slot Width: 0.250 inches First Leg Thickness:
First Leg Slot Width: 0.250 inches Second Leg Distance From Edge To Hole Center Along Width: 0.375 inches Second Leg Distance From Edge To Hole Center Along Length: 0.500 inches Second Leg Slot Length: 0.500 inches Second Leg Slot Width: 0.250 inches First Leg Thickness:
0.250 inches Second Leg Distance From Edge To Hole Center Along Width: 0.375 inches Second Leg Distance From Edge To Hole Center Along Length: 0.500 inches Second Leg Slot Length: 0.500 inches Second Leg Slot Width: 0.250 inches First Leg Thickness:
Second Leg Distance From Edge To Hole Center Along Width: 0.375 inches Second Leg Distance From Edge To Hole Center Along Length: 0.500 inches Second Leg Slot Length: 0.500 inches Second Leg Slot Width: 0.250 inches First Leg Thickness:
0.375 inches Second Leg Distance From Edge To Hole Center Along Length: 0.500 inches Second Leg Slot Length: 0.500 inches Second Leg Slot Width: 0.250 inches First Leg Thickness:
Second Leg Distance From Edge To Hole Center Along Length: 0.500 inches Second Leg Slot Length: 0.500 inches Second Leg Slot Width: 0.250 inches First Leg Thickness:
0.500 inches Second Leg Slot Length: 0.500 inches Second Leg Slot Width: 0.250 inches First Leg Thickness:
Second Leg Slot Length: 0.500 inches Second Leg Slot Width: 0.250 inches First Leg Thickness:
0.500 inches Second Leg Slot Width: 0.250 inches First Leg Thickness:
Second Leg Slot Width: 0.250 inches First Leg Thickness:
0.250 inches First Leg Thickness:
First Leg Thickness:
•
0.040 inches
Second Leg Thickness:
0.040 inches
First Leg Width:
0.750 inches
First Leg Distance From Edge To Hole Center Along Width:
0.375 inches
First Leg Distance From Edge To Hole Center Along Length:
0.312 inches
First Leg End Radius:
0.500 inches
Second Leg End Radius:
0.500 inches
First Leg Style:
End radius
First Leg Hole Arrangement Style:
One slot
Second Leg Style:
End radius
Second Leg Hole Arrangement Style:
One slot
Second Leg Relationship To First Leg:
Not identical

# NSN 5340-00-006-8177

Angle Bracket - Page 2 of 2



### First Leg Angle:

90.0 degrees

#### Material:

Steel comp 302

### Material Specification:

Mil-s-5059, annealed military specification single material response

#### Surface Treatment:

Passivate

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

---

#### **Demilitarization:**

No

Fiig:

A042a0

#### Mil-std (military Standard):

Mil-s-5059 spec.