

View Online at <https://aerobasegroup.com/nsn/5340-00-008-8871>

Mounting Hole Type:

Countersunk

First Leg Length:

0.625 inches

Second Leg Length:

0.625 inches

Second Leg Width:

3.312 inches

First Leg Hole Diameter:

Between 0.217 inches and 0.225 inches

Second Leg Hole Diameter:

Between 0.217 inches and 0.225 inches

Second Leg Distance Between Hole Centers Along Width:

Between 2.615 inches and 2.635 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.344 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.172 inches and 0.202 inches

First Leg Thickness:

0.375 inches

Second Leg Thickness:

0.375 inches

First Leg Width:

3.312 inches

First Leg Distance From Edge To Hole Center Along Width:

1.656 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.172 inches and 0.202 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Heat Treatment:

T-4 solution heat treated

Material:

Aluminum alloy 2024

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.