

View Online at <https://aerobasegroup.com/nsn/5340-00-009-3826>

**Thread Class:**

3a rod connection

**Thread Direction:**

Right-hand rod connection

**Thread Length:**

0.406 inches rod connection

**Shank Length:**

Between 1.638 inches and 1.644 inches

**Hole Diameter:**

Between 0.2500 inches and 0.2504 inches

**Shank Diameter:**

0.400 inches

**Overall Width:**

Between 0.550 inches and 0.560 inches

**End Radius:**

0.438 inches

**Fork Span Width:**

Between 0.260 inches and 0.265 inches

**Securing Pin Hole Diameter:**

Between 0.108 inches and 0.113 inches

**Distance From Center Of Securing Pin Hole To Rod End:**

0.200 inches

**Distance From Pivot Pinhole Center To Rod Connection End:**

Between 2.729 inches and 2.735 inches

**Fork Arm Thickness:**

0.150 inches

**Fork Depth:**

0.525 inches

**Shank Shoulder Diameter:**

Between 0.496 inches and 0.498 inches

**Thread Size:**

0.375 inches rod connection

**Special Features:**

Urethane, aliphatic, isocyanate, mil-c-83286,

**Material:**

Titanium alloy

**Material Specification:**

6al-6v-2sn, cage 26512 mfr ref single material response

**Style Designator:**

Clevis

**Test Data Document:**

81349-mil-i-6866 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unjf rod connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A264a0