

View Online at <https://aerobasegroup.com/nsn/5340-00-009-3826>

Thread Class:

3a rod connection

Thread Direction:

Right-hand rod connection

Thread Length:

0.406 inches rod connection

Shank Length:

Between 1.638 inches and 1.644 inches

Hole Diameter:

Between 0.2500 inches and 0.2504 inches

Shank Diameter:

0.400 inches

Overall Width:

Between 0.550 inches and 0.560 inches

End Radius:

0.438 inches

Fork Span Width:

Between 0.260 inches and 0.265 inches

Securing Pin Hole Diameter:

Between 0.108 inches and 0.113 inches

Distance From Center Of Securing Pin Hole To Rod End:

0.200 inches

Distance From Pivot Pinhole Center To Rod Connection End:

Between 2.729 inches and 2.735 inches

Fork Arm Thickness:

0.150 inches

Fork Depth:

0.525 inches

Shank Shoulder Diameter:

Between 0.496 inches and 0.498 inches

Thread Size:

0.375 inches rod connection

Special Features:

Urethane, aliphatic, isocyanate, mil-c-83286,

Material:

Titanium alloy

Material Specification:

6al-6v-2sn, cage 26512 mfr ref single material response

Style Designator:

Clevis

Test Data Document:

81349-mil-i-6866 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unjf rod connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A264a0