

View Online at <https://aerobasegroup.com/nsn/5340-00-011-4593>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.743 inches and 0.774 inches

Second Leg Length:

Between 1.665 inches and 1.696 inches

Second Leg Width:

1.542 inches

First Leg Hole Diameter:

Between 0.276 inches and 0.286 inches

Second Leg Hole Diameter:

Between 0.245 inches and 0.255 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 1.021 inches and 1.052 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.250 inches and 0.281 inches

First Leg Thickness:

Between 0.056 inches and 0.062 inches

Second Leg Thickness:

Between 0.056 inches and 0.062 inches

First Leg Width:

Between 1.842 inches and 1.904 inches

First Leg Corner Radius:

Between 0.250 inches and 0.281 inches

First Leg Distance Between Hole Centers Along Width:

1.342 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.250 inches and 0.281 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.250 inches and 0.281 inches

Second Leg End Radius:

Between 0.250 inches and 0.281 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Titanium alloy

Material Specification:

Ams 4910 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0