

View Online at <https://aerobasegroup.com/nsn/5340-00-011-4593>

**Fabrication Method (non-core):**

Machined

**First Leg Length:**

Between 0.743 inches and 0.774 inches

**Second Leg Length:**

Between 1.665 inches and 1.696 inches

**Second Leg Width:**

1.542 inches

**First Leg Hole Diameter:**

Between 0.276 inches and 0.286 inches

**Second Leg Hole Diameter:**

Between 0.245 inches and 0.255 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 1.021 inches and 1.052 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.250 inches and 0.281 inches

**First Leg Thickness:**

Between 0.056 inches and 0.062 inches

**Second Leg Thickness:**

Between 0.056 inches and 0.062 inches

**First Leg Width:**

Between 1.842 inches and 1.904 inches

**First Leg Corner Radius:**

Between 0.250 inches and 0.281 inches

**First Leg Distance Between Hole Centers Along Width:**

1.342 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.250 inches and 0.281 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.250 inches and 0.281 inches

**Second Leg End Radius:**

Between 0.250 inches and 0.281 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

End radius and tapered

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Titanium alloy

**Material Specification:**

Ams 4910 assn standard single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0