

View Online at <https://aerobasegroup.com/nsn/5340-00-012-0015>

**Fabrication Method:**

Formed

**First Leg Length:**

Between 0.600 inches and 0.620 inches

**Second Leg Length:**

Between 1.235 inches and 1.267 inches

**Second Leg Width:**

0.750 inches

**First Leg Hole Diameter:**

Between 0.214 inches and 0.224 inches

**Second Leg Hole Diameter:**

Between 0.401 inches and 0.411 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.375 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.375 inches

**First Leg Thickness:**

Between 0.056 inches and 0.068 inches

**Second Leg Thickness:**

Between 0.056 inches and 0.068 inches

**Center Section Height:**

Between 0.480 inches and 0.500 inches

**Center Section Width:**

0.500 inches

**Center Section Thickness:**

Between 0.056 inches and 0.068 inches

**First Leg Width:**

0.500 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**First Leg End Radius:**

0.250 inches

**Second Leg End Radius:**

0.375 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Angle:**

90.0 degrees

**Material:**

Steel comp 4130 and steel comp 8630

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams 2400 assn standard single treatment response

**Style Designator:**

Double angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0