## NSN 5340-00-013-7819

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-013-7819

| Mounting Hole Type:  |
|--|
| Plain  |
| First Leg Length:  |
| 0.620 inches   |
| Second Leg Length:   |
| 1.300 inches   |
| Second Leg Width:  |
| 1.428 inches   |
| First Leg Hole Diameter:                                   |
| 0.204 inches   |
| Second Leg Hole Diameter:                                  |
| 0.272 inches   |
| Second Leg Distance From Edge To Hole Center Along Width:  |
| 0.430 inches   |
| Second Leg Distance From Edge To Hole Center Along Length: |
| 0.250 inches   |
| First Leg Thickness:                                       |
| 0.080 inches   |
| Second Leg Thickness:                                      |
| 0.080 inches   |
| First Leg Width:   |
| 0.500 inches   |
| First Leg Distance From Edge To Hole Center Along Width:   |
| 0.250 inches   |
| First Leg Distance From Edge To Hole Center Along Length:  |
| 0.250 inches   |
| First Leg End Radius:                                      |
| 0.250 inches   |
| Second Leg End Radius:                                     |
| 0.370 inches   |
| First Leg Style:   |
| End radius   |
| First Leg Hole Arrangement Style:                          |
| One hole   |
| Second Leg Style:  |
| End radius   |
| Second Leg Hole Arrangement Style:                         |
| One hole   |
| Second Leg Relationship To First Leg:                      |
| Not identical  |
| First Leg Angle:   |

90.0 degrees

## NSN 5340-00-013-7819

Angle Bracket - Page 2 of 2

Material:

Mil-s-18729 spec.



| Steel comp 4130  |
|--|
| Material Specification:  |
| Mil-s-18729, cond a military specification single material response            |
| Surface Treatment:   |
| Cadmium  |
| Surface Treatment Specification:   |
| Qq-p-416, class 2, type 2 or 3 federal specification single treatment response |
| Style Designator:  |
| Angle  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A042a0   |
| Mil-std (military Standard):   |