

View Online at <https://aerobasegroup.com/nsn/5340-00-020-3348>

First Leg Length:

Between 0.760 inches and 0.780 inches

Second Leg Length:

Between 1.140 inches and 1.160 inches

Second Leg Width:

Between 0.820 inches and 1.060 inches

Second Leg Corner Radius:

Between 0.200 inches and 0.300 inches

First Leg Hole Diameter:

0.281 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.410 inches and 0.530 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.330 inches and 0.350 inches

Second Leg Slot Length:

Between 0.420 inches and 0.460 inches

Second Leg Slot Width:

Between 0.210 inches and 0.230 inches

First Leg Thickness:

Between 0.057 inches and 0.069 inches

Second Leg Thickness:

Between 0.057 inches and 0.069 inches

First Leg Width:

Between 1.790 inches and 1.830 inches

First Leg Corner Radius:

Between 0.220 inches and 0.240 inches

First Leg Distance Between Hole Centers Along Width:

1.350 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.220 inches and 0.240 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.220 inches and 0.240 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0