

View Online at <https://aerobasegroup.com/nsn/5340-00-023-9499>

Mounting Hole Type:

Plain

First Leg Length:

0.980 inches

Second Leg Length:

1.000 inches

Second Leg Width:

3.900 inches

First Leg Hole Diameter:

Between 0.265 inches and 0.270 inches

Second Leg Hole Diameter:

Between 0.203 inches and 0.207 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.000 inches

First Leg Thickness:

0.063 inches

Second Leg Thickness:

0.063 inches

Center Section Height:

0.870 inches

Center Section Width:

3.900 inches

Center Section Thickness:

0.063 inches

First Leg Width:

3.900 inches

First Leg Corner Radius:

0.250 inches

First Leg Distance Between First And Second Hole Centers Along Width:

1.500 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

1.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.440 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Three holes

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Special Features:

Second leg end concave

Material:

Aluminum alloy

Material Specification:

Qq-a-362 federal specification single material response

Surface Treatment:

Oxide film

Surface Treatment Specification:

-1l-c-5541 military specification single treatment response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

spec.